



Republic of the Philippines
VISAYAS STATE UNIVERSITY
 Visca, Baybay City, Leyte

PURCHASE REQUEST

Dept./Office: **ODPP**

Section/End-User: **Rafael Rosario A. Juntilla**

Funding Source: **General Fund - MOOE**

PR No.: **GF-2022-06-00713**

Date: **06-20-2022**

Category: **Electronics
supplies**

Project Title/Code: **PPES/PPO-2022**

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	1/4" Male Phone Str Mono Plug	pcs	20	400.00		8,000.00
Specification: <ul style="list-style-type: none"> • Male 1/4" Phone Str Mono Nickel • Number of positions (w/o PE): 2 • Rated current (40 °C) (A): 75 • Rated voltage (V): 25 						
2	3.5 mm 2-Pole Mono Phone Plug Connector	pcs	20	200.00		4,000.00
Specification: <ul style="list-style-type: none"> • Diecast Shell • For Cables 2.5 to 5mm Diameter • Precision-Machined Contacts • Quick Assembly 3 Piece Design 						
3	Adjustable Professional Tripod Lighting Stand	unit	4	7,000.00		28,000.00
Specification: <ul style="list-style-type: none"> • Adjustable Professional Tripod Stand (black) • Heavy Duty, Stable and sturdy • Light can stand can easily assembled • Can attach up to 4 lighting fixtures • Tripod legs can be adjusted • Tripod light stand height: approx. 122 cm with 2 more poles to extend height of the light stand • Light stand height can be extended to up approx. 210 cm • For lighting setups for any events 						
4	Battery Charger for AA and AAA with 4 AA NiMH rechargeable batteries included	unit	2	2,500.00		5,000.00
Specification: <ul style="list-style-type: none"> • Overcharge Protection: Limits damage to batteries from overcharge 						

<ul style="list-style-type: none"> • Safety Shut Off: Safety timer ensures charger is not active for extended periods of time • Bad Battery Detection: LED light will flash red when bad battery or non-rechargeable battery place in the charger. • Easy-to-read LED displays charging status • Red = Charging, Green = Good to Go! • “Bad battery” indicator light • Recharges 2 or 4 AA or AAA NiMH rechargeable batteries in 5 hours • With 4 AA NiMH Batteries included 						
5	Crank Up Lighting stand	unit	2	13,000.00		26,000.00
Specification: <ul style="list-style-type: none"> • Crank Up Lighting Stand • Features the Quick-N-Easy Gear Up for fast and easy adjustment. • All aluminum tubes and steel T-bar with clip for easy mounting construction reinforces and strengthens without excess weight. • Quick-N-Easy Gear Up for fast and simple adjustment square steel T-bar tubing for strength. • Length: 164-350cm(64.6-137.8") • Base diameter: 72.4" • Load capacity: 45 kg folded size 						
6	DMX 512 Intelligent Lighting Controller	unit	1	9,000.00		9,000.00
Specification: <ul style="list-style-type: none"> • Control up to 192 DMX Channels • 30 banks, each composed of 8 Programmable scenes. • 8 adjustable potentiometer to adjust the output size. • Built-in MIC head, and voice features. • Automatically trigger state, the TAP SYNC button or the SPEED potentiometer to determine automatically trigger time. • MIDI interface, may at any time using the MIDI signal control. • 4 LED digital display. • The first LED digitshows CHASES, the second digit led shows SCENES • The third and fourth led digit shows BANKS. • The second, third, fourth led digit show steps 0-255 or TIME. • BLACK OUT function can be used manually or MIDI remote control. • CHASES programming and CHASES run function can be used manually or MIDI remote control. • Output delay function, the FADE TIME potentiometer to adjust the delay time. • DMX output polarity selection. 						
7	Flight Case LED Par 8s	unit	4	8,500.00		34,000.00
Specification: <ul style="list-style-type: none"> • Fits for 8 pcs LED PAR Lights • Heavy Duty Honeycomb Design • Twist Lock • Heavy Duty Wheels • Aluminum Corners 						
8	Jack Connector 6.35 mm Cable Mount Stereo Plug, 3Pole 10A	pcs	20	400.00		8,000.00
Specification:						

<ul style="list-style-type: none"> • Male, 6.35 mm • Cable Mount • Type: Stereo • Body Orientation: Straight • Termination Method: Solder • Contact Plating: Nickel • Current Rating: 10A • Housing Material: Zinc Alloy • Contact Material: Brass • No of Poles/ Way: 3 						
9	Power Controller 10 Channel Audio	unit	1	3,000.00		3,000.00
Specification: <ul style="list-style-type: none"> • Power Controller 10 Channel Titanium audio • 10 lighted switches on front panel • 15 amps. resettable circuit breaker on front panel • 8 grounded AC sockets on rear of the unit • Maximum load: 15 amps Or 1800 watts 						
10	Stage Light Outdoor RGB 18 x 18 flat Par LED Mini	set	8	7,000.00		56,000.00
Specification: <ul style="list-style-type: none"> • Stage Light Outdoor RGB 18 x 18 Flat Par LED mini 64 warm White • Color Temperature: 3500k(warm White) 						
11	Stage Lights Bar, Yeesite 72W 24LEDs RGB Wash Lights DMX Control LED	set	8	5,500.00		44,000.00
Specification: <p>Stage Lights Bar, 72W 24LEDs RGB Wash Lights DMX LED Wall Washer Light Uplight</p> <p>40 inch Long Professional grade indoor linear bar powered 24x3-Watt LEDs</p> <p>Light Source: 24 TRI LEDs(RGB)</p> <p>Power Draw: 72 watts</p> <p>40- degree beam angle provides vibrant and broad light beam to wash stage, wall and dance floor</p> <p>Power Linking: Max 10 units at 120 Volts or 27 units at 230Volts</p>						
12	Transmitter Receiver Kit portable (4 pcs)	pcs	2	6,500.00		13,000.00

Specification: <ul style="list-style-type: none"> • Transmitter Receiver Kit Portable 2.4G ISM Wireless Stage Light lighting fixtures • High effective GFSK module, communication design; 126 channels jumping frequency automatically, high • anti-jamming ability, to ensure that works reliability 						
13	Waterproof LED Parabolic Aluminized Reflector (PAR) Lights for Stage Events	set	20	3,000.00		60,000.00
Specification: <ul style="list-style-type: none"> • Light Source:18X18w RGBWA • Beam Angle: 25 Degree • Waterproof: IP65 • Housing: Aluminum • Style :DMX Stage Light • Power:300W • Color: 6000k(daylight) 						
14	Wireless Microphone Mic System, 2.4G, 6 channels	unit	2	15,000.00		30,000.00
Specification: <ul style="list-style-type: none"> • 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery • Compact size 2.4G wireless microphone system, XLR connection, easy to use • less than 4ms ultra-low latency, clear and stable signal transmission • 32bit/48Khz high resolution audio quality • Built -in rechargeable lithium battery 						
15	XLR 3 Pole Female, Stamped Contacts, Nickel Finish	pcs	60	300.00		18,000.00
Specification: <ul style="list-style-type: none"> • XLR 3 pole female, stamped contacts, nickel finish. • Ergonomic stylish sleeve design for improved grip. • Oversized latch lever preserves your thumb. Leading first mate last break pin 1 on socket connectors. • Chuck style cable clamp to suit 3mm - 8mm (0.118" - 0.314") cable. • Overmolded cable support boot • Precision machined pin contacts • Compact 2.5mm (14AWG) solder buckets • Zinc diecast shell housing with Satin nickel finish. 						
16	XLR male connector	pcs	60	500.00		30,000.00
Specification: <ul style="list-style-type: none"> • Standard XLR Male 3pin • Nickel Contact Plating • Mating Cycles: 1000 Cycle 						
	TOTAL					376,000.00
Purpose: For PPES Personnel's equipment						

Checked by:		Funds Available:	
MICHAEL ANTHONY JAY B. REGIS		ALICIA M. FLORES	
TWG - Electronics supplies		HEAD, BUDGET OFFICE	
Signature: Printed Name: Designation:	Requested by:	Noted by:	Approved by:
	RAFAEL ROSARIO A. JUNTILLA	MARLON G. BURLAS	EDGARDO E. TULIN
	END USER	UNIT HEAD, PROJECT LEADER	PRESIDENT, VSU