

Republic of the Philippines
VISAYAS STATE UNIVERSITY
Visca, Baybay City, Leyte
SUPPLY & PROPERTY MANAGEMENT

INSPECTION & ACCEPTANCE REPORT

Supplier: **KRYPTON INTERNATIONAL RESOURCES SALES & SERVICES INC.** IAR No: 25-07-0835
P.O No.: **VSU-GOODS-BAC2-24-64-011 (TF)** Date: 2025-05-07
Office/Dept: **NARC** 107,000.00 TF-2024-09-01663

| No. | UNIT | DESCRIPTION | Quantity | | Date Received | Balance | Remarks |
|-----|------|--|----------|--------|-------------------------------------|---------|-----------|
| | | | Per P.O | Actual | | | |
| 1 | unit | Bead sterilizer with glass beads for laboratory supply-beads, OFFER: Biobase/ GBS300-H | 2 | 2 | 2025-05-07 #: DR-28093/SI-024518 | 0 | Completed |

Specification:

Speci?cation:

Description:

Function: Uses heated glass beads for rapid sterilization of small lab equipment such as forceps, scissors, scalpels, needles, and inoculation needles.

Sterilization Time: E?ective within ten seconds

Heating Temperature: Approximately 300°C

Common Use: Research laboratories

Features:

1. Compact Design: Ideal for use in ultraclean workbenches; digital display shows real-time temperature.

2. Material & Build:

Inner Container: Stainless steel

Heating Element: High-performance

Temperature Controller: High precision with over-temperature protection

3. Temperature Control: Equipped with high-temperature sterilization beads.

4. Size and Weight: Small volume, lightweight, simple to operate, and a long working life.

5. Glass Beads Con?guration: Diameter of 2.0-2.5 mm

Technical Parameters:

Temperature Control Range: 100°C - 300°C

Temperature Stability: ±5°C

Heating Speed: 225 minutes

Heating Well Volume: Diameter 40 mm, Depth 140 mm

Glass Beads Capacity: At least 300 g

Cover Material: Stainless steel

Insulation Material: NOT INDICATED

Electrical Specifications:

Voltage: AC 220V 50Hz or AC 110V 60Hz

Power: 250W

Fuse: 250V, 2A/3A, 75 x 20 mm

Dimensions & Weight:

Dimension (W x D x H): Approx. 176 x 135 x 249.5 mm

Net Weight: Approx. 3.3 kg

| | | | | | | | |
|---|------|----------------------------|---|---|-------------------------------------|---|-----------|
| 2 | unit | Emergency Eye Wash station | 1 | 1 | 2025-05-07 #: DR-28093/SI-024518 | 0 | Completed |
|---|------|----------------------------|---|---|-------------------------------------|---|-----------|

Specification:

Description:

- **Purpose:** Suitable for cleaning eyes, face, and hands; spray head can be used for washing the whole body.

Operation:

- **Spray Shower:** Controlled by the top of the handle.
- **Flow:** Steady and ample.
- **Valve-Switch Operation:** Simple, touch the knob to use.

Design:

- **Ergonomics:** Height and angle of the bowl are designed to fit the face proportion.
- **Water Outlet:** Designed to make the water flow mild, protecting the eyes.
- **Drainage System:** Allows used water to flow directly through a tube in the bowl, minimizing pollution.

Material:

- **Construction:** Stainless steel, firm, and chemical resistant.

Dimensions and Weight:

- **Package Size (W x D x H):** 1310 mm x 380 mm x 250 mm
- **Gross Weight:** 17.5 kg

Installation:

- **Service:** Free installation at the project site with a ready water supply.

INSPECTION

5/8/15

ACCEPTANCE

5/8/15

Date Inspected:

Date Recieved:

☐ Inspected, verified and found in order
as to quantity and specifications

☒ Complete

☐ Others: _____

☐ Partial

NOREVE JEAN M. AGAD

Inspector

VIVIAN V. BALBARINO

Head, Supply & Property Management