Republic of the Philippines

VISAYAS STATE UNIVERSITY

Visca, Baybay City, Leyte

SUPPLY & PROPERTY MANAGEMENT

INSPECTION & ACCEPTANCE REPORT

Supplier:

LEYTE PAPERWORLD

IAR No:

25-09-1123

P.O No.: VSU-GOODS-25-25-160 (STF)

Date:

2025-09-09

Office/Dept: Assorted Depts/Offices

438,364.00

Assorted PR's

No.	UNIT	NIT DESCRIPTION	Qua	ntity	Date Received	Balance
			Per P.O	Actual		
1	unit	Electric Paper Shredder, DELI Distribution CAFS c/o Remenita J. Solis (STF-2024-10-02352) - 1	1	1	2025-09-08 #: DR- 22305,22307,22306,22308,22309	0

Specification:

- . Shredding Capacity: Up to 16 sheets; <10 sheets per shred
- · Shredding Medium:
 - · Photo
 - o Card
 - o CD
 - o Paper
- · Capacity: <50L
- · Power: 400W
- · Shredder Type: Cross-Cut
- Security Grade: S4
- Volume: 30L
- · Feeding Method: Infrared automatic paper feeding

2	unit	GPS Navigator Touchscreen, GARMIN Distribution DFS c/o Erale Jane P. Manzano (STF-2024-10-02556) - 1 DFS c/o Erale Jane P. Manzano (STF-2024-10-02556) - 1	2	2	2025-09-08 #: DR- 22305,22307,22306,22308,22309	0	C
---	------	---	---	---	--	---	---

Specification:

- Type: 2-Way Radio/GPS Navigator with Touchscreen
- · Power:
 - o Removable, rechargeable lithium-ion battery pack
 - AA battery pack compatibility
- Water Rating: IPX7
- · Sensors:
 - o GPS
 - GLONASS

		Barometric altimeter					
		Maps:					
		 Preloaded basemap 					
		 Ability to add maps 					
		Warranty: 1 year					
3	unit	LCD Projector (XGA), EPSON Distribution DABE c/o Lorbert G. Mazo (STF-2024-10-02264) - 1	1	, 1	2025-09-08 #: DR- 22305,22307,22306,22308,22309	0 .	
	Specifi	cation:		- hours		Mary Salvania	Γ
		Projection System: 3LCD Technology, RGB liquid	crystal shutter				
		Resolution: SVGA (800x600), 4:3 aspect ratio					
	•	Light Output: 3,300 Lumen (standard mode), 2,05	0 Lumen (econo	my mode)			
1		Contrast Ratio: 15.000:1					

			LCD Projector (XGA), EPSON			2025-09±08		
1	4	unit	Distribution DBM c/o Shellio G. Catorce (STF-2024-10-03023) - 1 ITEEM c/o Shaira B. Manapsal (STF-2024-10-02337) - 2	3	3	#: DR- 22305,22307,22306,22308,22309	0 .	•

Specification:

Projection System:

Lamp: 210 W

• Lamp Hours: 6,000 to 10,000 hours

Technology:

RGB Liquid Crystal Shutter Projection System (3LCD), 3-Chip Technology

Light Output:

- White Light Output (Normal/Eco): 3,600 lm
- · Colour Light Output: 3,600 lm

Resolution:

XGA, at least 1024 x 768

Aspect Ratio:

• 4:3

LCD:

- Native Resolution: XGA (1024 x 768)
- Size: 0.55" (C2fine)

Lightsource:

- Type: 210W UHE
- · Life (Normal / Eco): 6,000 / 12,000 hours

Inputs:

. Analog Input: D-Sub 15pin: 1

. Digital Input: HDMI: 1

USB Interface:

• USB Type B: 1 (For Firmware Update, Copy OSD Settings)

5	unit	LCD Projector (XGA), EPSON Distribution DSO c/o Junard C. Gucela (STF-2024-10-02965) - 1	1	, 1	2025-09-08 #: DR- 22305,22307,22306,22308,22309	0	(
---	------	--	---	-----	--	---	---

Specification:

Projection System Technology:

• Type: RGB Liquid Crystal Shutter Projection System (3LCD), 3-chip technology

Light Output:

• White Light Output (Normal/Eco): 3,600 lm

. Colour Light Output: 3,600 lm

Resolution:

• Native Resolution: XGA (1024 x 768)

. Aspect Ratio: 4:3

LCD Panel:

• Size: 0.55" (C2fine)

Light Source:

• Type: 210W UHE

• Life (Normal / Eco): 6,000 / 12,000 hours

Inputs:

· Analog Input: D-Sub 15pin (1)

· Digital Input: HDMI (1)

USB Interface:

• Type: USB Type B (1) - For Firmware Update, Copy OSD Settings

6	unit	Powered Speakers, 2-way, 12" with bluetooth and Wall mount, JBL Distribution JEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 2	2	2	2025-09-08 #: DR- 22305,22307,22306,22308,22309	0	c
---	------	---	---	---	--	---	---

Specification:

Powered Speaker

- Coverage Pattern (Nominal)100° x 60°
- Frequency Response Hz (±3 dB)60 20,000
- Maximum SPL (peak dB)127
- Power Rating (W, Continuous)650
- Power Rating (W, Peak)1300
- BluetoothYes
- Feedback suppressionYes
- M10 suspension pointsYes
- · Mobile app available for iOS and Android: Yes
- · Music Ducking: Yes
- Single-angle pole-mount socket Yes

Wall Mount

- · Up to 50 Kg Speaker Capacity
- · Standard Fit to all speaker's with hole
- · For wall mounting pro speakers with pole mount.
- · Heavy Duty
- · Includes Expansion bolt for wall mounting on concrete

7 Set Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00004) - 1 LDHRAO c/o Jonathan Eduard S. Cabal (STF-2024-10-02526) - 1	2	2	2025-09-08 #: DR- 22305,22307,22306,22308,22309	0 .	
---	---	---	--	-----	--

Specification:

Product Features:

• Frequency Range: 683.1 MHz to 695.1 MHz

· Selectable Frequencies: 20 frequencies available

· Casing Material: ABS

· Low Battery Indicator: Yes

· Operational Distance: Up to 30 meters

. Frequency Switching: Easy operation for frequency adjustment

Device Compatibility: Can connect with mobile phones and other electronic devices

Technical Specifications:

· Oscillation Mode: DSP chips frequency locking

• Frequency Stability: +10 ppm

RF Efficiency: 10 dBm
 Distortion: <0.65 dB

• Battery Type: 3.7V Lithium (400 mAh)

8	pc	Water Dispenser, Cabinet type, FUZIDENZO Distribution UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03145) -	1	1	2025-09-08 #: DR- 22305,22307,22306,22308,22309	0	C
---	----	--	---	---	--	---	---

Specification:

. Type: Floor Standing Functions: o Hot o Cold . Body Material: Plastic . Compressor: High Efficiency · Protection: Thermally Protected Wireless Dual Handheld Microphone, CAROL Undelivered 1 9 set LDHRAO c/o Jonathan Eduard S. Cabal (STF-2024-10-02530) -Specification: Receiver o Power Consumption: 12w (Max) · Receiver Sensitivity: -95dbm Mixing Output Socket: ø6.3mm Socket Balanced Output Socket: XLR Socket Transmitter o Carrier Frequency: Depends on regional frequency band o Transmit Power: 10dBm (±2dBm) o Microphone Capsule: Dynamic o Polar Pattern: Super Cardioid o Impedance: 600o Frequency Response: 80~12000Hz Current Consumption: 120mA Battery: Size AA x 2pcs o Operation Range: 90 meters (in open area) o Battery Life: Approximately 12 hours (uses alkaline batteries) · Each microphone has 100 selectable channels and independent volume controls. This UHF system features 6-axis gyroscope to automatically enter mute mode when idling for 5~10 seconds. Wireless Microphone (2pcs) with Receiver, SHURE Undelivered 0 10 unit Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00004) - 1 Specification: . Simultaneous Systems Per Band: Up to 12 · System: o Type: Analog o Frequency Range: 542-572 MHz Operating Range: 300 ft. Line-of-sight Frequency Response: 50Hz-15kHz · Channel Selection: Auto/Manual · Microphone: o Type: Dynamic o Polar Pattern: Cardioid

ACCEPTANCE	
Date Recieved: glater	
Complete	
- Partial	
	1%
DOREEN B. ALBA	
	Date Recieved: glats Complete Partial