Republic of the Philippines

VISAYAS STATE UNIVERSITY

Visca, Baybay City, Leyte

SUPPLY & PROPERTY MANAGEMENT

INSPECTION & ACCEPTANCE REPORT

Supplier:

ELECTROCOMPUTER DATA SYSTEM (EDS)

IAR No:

25-09-1080

P.O No.:

VSU-GOODS-25-25-179 (STF)

Date:

2025-09-02

Office/Dept: Assorted Depts/Offices

101,860.00

Assorted PR's

No.	UNIT	DESCRIPTION	Qua	Quantity		D-1	Domesto
			Per P.O	Actual	Received	Balance	Remarks
1	unit	4k Quantum Smart TV, DEVANT Distribution CFES c/o Jesibel L. Muertigue (STF-2024-10-02589) - 1	1	0		1,	Undelivered

Specification:

4K Quantum Smart TV

· Size: 55 inches

• Display Resolution: Ultra HD 3840x2160

- · Features:
 - Dolby Vision
 - Dolby Atmos
 - · HDR10
 - o Built-in ISDB-T Receiver
 - · Wifi/LAN
 - Bluetooth Function
 - Anyview Cast/Screen Sharing
- USB: 2.0

		Bottom Loading Water Dispenser, KAISA				
2	pc	Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00004) - 1	1	0	1	Undelivered

Specification:

Product Model: JD-8044

• Voltage/Frequency: 220V ~ 50Hz

Cooling Power: 75W

· Heating Power:

Warm & Hot: Rated Power: 425WCold & Hot: Rated Power: 500W

· Heating Power: 425W

Carton Size: 355 x 325 x 1040 mm

		Actual Product Size: 320 x 285 x 980 mm Hot Water Temperature Range: 85 - 95°C			-		
3	unit	Coffee Maker, 12 Cups, IMARFLEX Distribution CN c/o Guada Fe D. Amihan (STF-2024-10-02662) - 1	1	0		1	Undelivered

Specification:

Capacity: 12 Cups
Carafe: Thermo Glass
Panel: Stainless Steel

. Display: LCD Time Display

• Features: Aroma Control, Automatic Drip Coffee, Keep Warm Heater Plate

Filter: Washable Filter Basket
Water Level Indicator: Yes

· Cord Storage: Yes

Color Options: Black / Gray

· Warranty: 1 Year on Electrical Parts

· Power:

Voltage: 230 V AC, 60 HzConsumption: 900 Watts

Dimensions:

Net: 263.4 x 183.5 x 339.4 mm
 Gross: 286.0 x 194.0 x 368.0 mm

· Weight:

Net: 1.80 kgGross: 2.23 kg

. Included in the Box: Manual & Warranty Card, Scoop, Filter Basket, Carafe

		Heavy Duty Vacuum Cleaner, STANLEY					
4	рс	Distribution CN c/o Guada Fe D. Amihan (STF-2024-10-02662) - 1	1 .	1	2025-09-01 #: CI-226527	0	Completed

Specification:

- Powerful motor provides maximum power for suction and blowing
- · Sturdy handle for easy carrying
- · Large water-resistant on-off switch
- · 3 m power cord with cord-wrap design
- · Swiveling casters for ease of movement in all directions
- 10-piece accessory kit included: foam filter, gulper nozzle, 3 extension wands, floor nozzle, crevice nozzle, disposable filter bag, reusable cloth filter, mounting ring and 1.50 m x 3.20 cm hose
- · Capacity: 5 gallon
- Power: 1000 W
- Voltage: 220 V 60 Hz
- Dimension: L 37 x W 37 x H 48 cm

		Laminator Machine, A3, A3 OFFICOM					
5	unit	Distribution	1	1	2025-09-01 #: CI-226527	0	Completed
		CAFS c/o Remenita J. Solis (STF-2024-10-02355) - 1			#. CI-220327		
5	pecific	cation:					L.,
		Type: Laminator Machine					
		Size Compatibility: A3 & A4					
		Features:					
		Heavy-duty construction					
		 Infrared heating system 					
		Adjustable temperature control					
		 Overheating protection 					
		Smart TV Smart Quantum 4k, 55", DEVANT					
	te	W 80 82	1	0			Undelivered
6	unit	Distribution AdO c/o Rubelyn P. Fernandez (STF-2024-10-02920) - 1		0	, ,	1	Undelivered
7.2							
,	pecifi	cation:					
	Gene	ral Specifications				•	
		Size: 55 inches					
		Backlight: Direct LED					
		Operating System: Vidaa U					
		Display Resolution: Ultra HD 3840 x 2160					
		Power Requirement: 100-240V 50/60Hz AC					
		Power Consumption: 150W					
		Management of the selection of					
		Warranty: Included					
		Studio Monitors, 2-way active (Pair Left and					
7	set	Studio Monitors, 2-way active (Pair Left and	1	0		1	Undelivered
7		Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS	1	0		1	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS	1 ,	0		1	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marion V. Dampios (STF-2024-10-02464) - 1 cation:	1	0		1	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02454) - 1 cation: Frequency Response: 70 Hz-20 Khz	1	0		1	Undelivered
	set Specific	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marion V. Dampios (STF-2024-10-02464) - 1 cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker	1	0		1	Undelivered
	set Specific	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02464) - 1 Cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB	1	0		1	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02464) - 1 cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB LF Driver: 4.5" Kevlar	1	0		1.	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marion V. Dampios (STF-2024-10-02464) - 1 Cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB LF Driver: 4.5" Kevlar Kevlar woofer and low-mass silk-dome tweeter	1	0		1	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02464) - 1 cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB LF Driver: 4.5" Kevlar Kevlar woofer and low-mass silk-dome tweeter Input Impedance: 10 K ohms	1	0		1.	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marion V. Dampios (STF-2024-10-02464) - 1 Cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB LF Driver: 4.5" Kevlar Kevlar woofer and low-mass silk-dome tweeter	1	0		1	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02464) - 1 cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB LF Driver: 4.5" Kevlar Kevlar woofer and low-mass silk-dome tweeter Input Impedance: 10 K ohms Power: 100-120V-50/60 Hz Monitor calibration	1	0		1	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02464) - 1 Cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB LF Driver: 4.5" Kevlar Kevlar woofer and low-mass silk-dome tweeter Input Impedance: 10 K ohms Power: 100-120V-50/60 Hz Monitor calibration 25W Class AB amplification per speaker		0		1	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02464) - 1 Cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB LF Driver: 4.5" Kevlar Kevlar woofer and low-mass silk-dome tweeter Input Impedance: 10 K ohms Power: 100-120V-50/60 Hz Monitor calibration 25W Class AB amplification per speaker Balances 1/4" TRS, unbalance 1/8" TS, RCA, and bare		0		1	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02464) - 1 Cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB LF Driver: 4.5" Kevlar Kevlar woofer and low-mass silk-dome tweeter Input Impedance: 10 K ohms Power: 100-120V-50/60 Hz Monitor calibration 25W Class AB amplification per speaker Balances 1/4" TRS, unbalance 1/8" TS, RCA, and bare 1/8" stereo headphone output		0		1.	Undelivered
	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02464) - 1 Cation: Frequency Response: 70 Hz-20 Khz LF amplifier: 5 W/speaker Peak SPL (@1 meter): 100dB LF Driver: 4.5" Kevlar Kevlar woofer and low-mass silk-dome tweeter Input Impedance: 10 K ohms Power: 100-120V-50/60 Hz Monitor calibration 25W Class AB amplification per speaker Balances 1/4" TRS, unbalance 1/8" TS, RCA, and bare	-wire inputs	0		1	Undelivered

Date Inspected: aluly	Date Recieved:	
Inspected, verified and found in order as to quantity and specifications	Complete	
Others:	Partial	
40/#	J. Jul	
JUDE B. ROLA Inspector	Head, Supply & Property Management	

.