

Republic of the Philippines
VISAYAS STATE UNIVERSITY
Visca, Baybay City, Leyte
SUPPLY & PROPERTY MANAGEMENT

INSPECTION & ACCEPTANCE REPORT

Supplier: **REDSEA AGRO INDUSTRIAL CORP**
P.O No.: **VSU-GOODS-23-39-R-365**
Office/Dept: **PCC**

IAR No: 25-09-1089
Date: 2025-09-05
1,398,000.00 TF-2023-08-02051

No.	UNIT	DESCRIPTION	Quantity		Date Received	Balance	Remarks
			Per P.O	Actual			
1	unit	BATCH PASTEURIZER	2	2	2025-09-02 #: DR-5139,5140	0	Completed

Specification:

Batch Pasteurizer Specifications

- Capacity: 100 liters
- Construction:
 - Material: 3-walled SS304 tank
 - Inside Thickness: 2.5 mm
 - Outside Cladding: 1.5 mm with insulation
- Service Connections:
 - Inlet/Outlet: 25 mm for hot water
- Agitation and Heating:
 - Geared Motor: 0.37 kW, 220V, 60Hz, 1P
 - Agitator: Slow
 - Temperature Indicator: 0-120°C
- Valves and Covers:
 - Product Outlet: 1.5" sanitary butterfly valve
 - Cover: Removable, motor-controlled
- Hot Water System:
 - LPG Hot Water Set: High-pressure burner
 - Hot Water Circulating Pump: Working temperature up to 110°C

Documentation Components

- Owner/User Manual
- Operations Manual
- Maintenance Manual
- Spare Parts List

Training

- **Training:** Administered upon delivery and installation, including testing and commissioning of the equipment.

Warranty Components

- **Coverage:** Parts (excluding consumable parts) and technical services for one (1) year from the date of delivery and acceptance.
- **Service:** Replacement of defective parts, regular check-ups, consultation, and maintenance services at no cost to PCC during the warranty period.

After Sales Service

- **Spare Parts Guarantee:** Availability of spare parts and components for at least five (5) years from the date of acceptance, regardless of maintenance agreements.

2	unit	FIBER REINFORCED PLASTIC INSULATED TANK	2	2	2025-09-02 #: DR-5139,5140	0	Completed
---	------	---	---	---	-------------------------------	---	-----------

Specification:

Fiber Reinforced Plastic Insulated Tank Specifications

- **Capacity:** 500 liters
- **Insulation:**
 - **Material:** Polyurethane
 - **Thickness:** 2 inches
- **Piping:**
 - **Type:** Insulated
 - **Size:** 1" PPR piping
 - **Purpose:** From IBU to PHE/Holding tank
- **Base:**
 - **Type:** Skid base
 - **Material:** 100mm C-channel

Documentation Components

The supplier/contractor shall provide the following documents/manuals in English:

1. Owner/User Manual
2. Operations Manual
3. Maintenance Manual
4. Spare Parts List

Training

- **Training** will be provided upon delivery and installation, including testing and commissioning of the equipment.

Warranty Components

- **Warranty Duration:** 1 year from the date of delivery and acceptance (evidence by a Certificate of Final Acceptance issued by the PCC/end-user).
- **Coverage:** Parts (excluding consumable parts) and technical services.

- **Services Included:** Replacement of defective parts, regular check-ups, consultation, and maintenance services at no cost during the warranty period.

After Sales Service

- **Spare Parts Availability:** The supplier must guarantee the availability of spare parts and components for at least five (5) years from the date of acceptance of the equipment, regardless of any maintenance agreements.

3	unit	HOLDING TANK	2	2	2025-09-02 #: DR-5139,5140	0	Completed
---	------	--------------	---	---	-------------------------------	---	-----------

Specification:

Holding Tank Specifications

- **Capacity:** 100 liters
- **Material:** 3-walled SS304
 - **Inside Thickness:** 2.5 mm
 - **Outside Cladding:** 1.5 mm with insulation
- **Service Inlet/Outlet:** 25 mm for cooling water
- **Agitator:**
 - **Type:** Slow agitator
 - **Motor:** 0.37 kW, 220V, 60Hz, 1P geared motor
- **Temperature Indicator:** 0-120°C
- **Product Outlet:** 1.5" sanitary butterfly valve
- **Cover:** Removable, motor-controlled
- **Raw Water Circulating Pump:**
 - **Power:** 1 HP
 - **Voltage:** 220V, 1P

Documentation Components

The supplier/contractor shall provide the following documentation/manuals in English:

1. **Owner/User Manual**
2. **Operations Manual**
3. **Maintenance Manual**
4. **Spare Parts List**

Training

- **Training** will be provided upon delivery and installation, including testing and commissioning of the equipment.

Warranty Components

- **Warranty Duration:** 1 year from the date of delivery and acceptance (evidence by a Certificate of Final Acceptance issued by the PCC/end-user).
- **Coverage:** Parts (excluding consumable parts) and technical services.
- **Services Included:** Replacement of defective parts, regular check-ups, consultation, and maintenance services at no cost during the warranty period.

After Sales Service

- **Spare Parts Availability:** The supplier must guarantee the availability of spare parts and components for at least five (5) years from the date of acceptance of the equipment, regardless of any maintenance agreements.

4	unit	MILK PUMP	2	2	2025-09-02 #: DR-5139,5140	0	Completed
---	------	-----------	---	---	-------------------------------	---	-----------

Specification:

Milk Pump Specifications

- **Power:** 1 HP
- **Voltage:** 220V, 1 Phase
- **Material:** SS304
- **Features:**
 - Simple structure
 - Easy to clean and dismantle
 - Highly sealed
 - Low noise
 - Lightweight
 - Self-lubricating

Documentation Components

The supplier/contractor shall provide the following documentation/manuals in English:

1. **Owner/User Manual**
2. **Operations Manual**
3. **Maintenance Manual**
4. **Spare Parts List**

Training

- **Training** will be provided upon delivery and installation, including testing and commissioning of the equipment.

Warranty Components

- **Warranty Duration:** 1 year from the date of delivery and acceptance (evidence by a Certificate of Final Acceptance issued by the PCC/end-user).
- **Coverage:** Parts (excluding consumable parts) and technical services.
- **Services Included:** Replacement of defective parts, regular check-ups, consultation, and maintenance services at no cost during the warranty period.

After Sales Service

- **Spare Parts Availability:** The supplier must guarantee the availability of spare parts and components for at least five (5) years from the date of acceptance of the equipment, regardless of any maintenance agreements.

5	unit	PLATE HEAT EXCHANGER	2	2	2025-09-02 #: DR-5139,5140	0	Completed
---	------	----------------------	---	---	-------------------------------	---	-----------

Specification:

Plate Heat Exchanger Specifications

- **Capacity:** 500 L per hour
- **Material:** SS316
- **Plate Thickness:** 0.6 mm
- **Service Line Outlet/Inlet:** 25 mm
- **Gasket Material:** Nitrile Rubber

Documentation Components

The supplier/contractor shall provide the following documentation/manuals in English:

1. **Owner/User Manual**
2. **Operations Manual**
3. **Maintenance Manual**
4. **Spare Parts List**

Training

- **Training** will be provided upon delivery and installation, including testing and commissioning of the equipment.

Warranty Components

- **Warranty Duration:** 1 year from the date of delivery and acceptance (evidence by a Certificate of Final Acceptance issued by the PCC/end-user).
- **Coverage:** Parts (excluding consumable parts) and technical services.
- **Services Included:** Replacement of defective parts, regular check-ups, consultation, and maintenance services at no cost during the warranty period.

After Sales Service

- **Spare Parts Availability:** The supplier must guarantee the availability of spare parts and components for at least five (5) years from the date of acceptance of the equipment, regardless of any maintenance agreements.

INSPECTION

Date Inspected: 9/5/14

☐ Inspected, verified and found in order as to quantity and specifications

☐ Others: _____

ACCEPTANCE

Date Recieved: 9/5/14

☐ Complete

☒ Partial

NOREVE JEAN M. AGAD
Inspector

DOREEN B. ALBA
Head, Supply & Property Management