

Republic of the Philippines  
**VISAYAS STATE UNIVERSITY**  
Visca, Baybay City, Leyte  
**SUPPLY & PROPERTY MANAGEMENT**

2nd IAR

## INSPECTION & ACCEPTANCE REPORT

Supplier: **ELECTROCOMPUTER DATA SYSTEM (EDS)** IAR No: 25-09-1097  
P.O No.: **VSU-GOODS-25-26-214 (STF)** Date: 2025-09-08  
Office/Dept: **Assorted Depts/Offices** 1,907,166.50 Assorted PR's

No.	UNIT	DESCRIPTION	Quantity		Date Received	Balance	Remarks
			Per P.O	Actual			
1	unit	12" 500Watts Active Speaker System USB/ BLUETOOTH Function, includes Speaker wallmount, Kevler ZLX12D 12" <div>Distribution DCST c/o Michael D. Dag-uman (STF-2024-10-02544) - 1</div>	1	0		1	Undelivered

### Specification:

- 12" active speaker system
- Provide excellent vocal and bass performance
- Rugged plastic mold design cabinet
- Bottom pole mount for tripod stand
- USB / Bluetooth Functions
- Multiple handle for easy transport
- 90 X 60 degrees wave guide horn for wide coverage
- Multi angle enclosure can also use a monitor
- Line level and direct mic input
- DSP management control w/ 5 preset settings Normal, DJ, Voice, Live, Flat
- System Type: 2 Way Bass Reflex
- LF: 12" woofer (2.5" Voice coil size)
- HF: 1.7" Polymide Dome Tweeter
- Freq Response: 45Hz-20KHz
- Amp Power: 500W Class D
- Input Impedance: 20K ohms
- Input Gain: line: +20dBu/Mic: +40dB
- Input Connector: Live (RCA & XLR combo jack)
- Output Connector: Line (XLR loop through)
- THD: Less than 0.5%
- LED Indicator: Power, Signal, Clip
- Crossover Frequency: 2.5KHz
- AC Input: 220V 50-60Hz
- Speaker Stand Wall Mount Specs
  - Wall Mounting Speaker Pole

- Multi Angle Adjustability
- Foam Padded Speaker
- Base Plate Adjusts from 5.5" to 10.5"
- Rubberized Mounting Surface To Protect Your Speaker From Scratches
- 35mm (1.38") Diameter Speaker Mount
- Can Hold Speaker Up To 150 lbs (68.2kg)

2	unit	<b>2 Line VOIP Phone, Yealink SIP-T31G</b>  Distribution UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03144) - 2	2	0		2	Undelivered
---	------	--	---	---	--	---	-------------

#### Specification:

(Must be compatible with existing fleet of VOIP Phone and Yeastar S300 Server)

1 Year Warranty

#### Audio Features

- HD voice: HD handset, HD speaker
- Smart Noise Filtering
- Narrowband codec: PCMU (G.711A), PCMA (G.711?), G.723.1, G.729, G.729A, G.729B, G.729AB, G.726, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP

#### INFO

- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

#### Phone Features

- 2 VoIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Redial, call return, auto answer
- Local 5-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete

- Set date time manually or automatically

- Dial plan

- XML Browser, action URL/URI

- Integrated screenshots

- RTCP-XR, VQ-RTCPXR

- Enhanced DSS Key

#### Directory

- Load phonebook up to 1000 entries

- Black list

- XML/LDAP remote phonebook

- Smart dialing

- Phonebook search/import/export

- Call history: dialed/received/missed/forwarded

#### IP-PBX Features

- Busy Lamp Field (BLF), Bridged Line Appearance

#### (BLA)

- Anonymous call, anonymous call rejection

- Hot-desking, voice mail

- Flexible seating

- Call park, call pickup

- Executive and Assistant

- Centralized call recording

- Visual voice mail

- Call recording

#### Display and Indicator

- 2.3" 132x64-pixel graphical LCD with backlight

- LED for call and message waiting indication

- Dual-color (red or green) illuminated LEDs for

line status information

- Intuitive user interface with icons and soft keys

- Multilingual user interface

- Caller ID with name and number

- Power saving

#### Feature keys

- 2 line keys with LED

- 6 features keys: transfer, message, headset,

redial, mute, hands-free speakerphone

- 5 navigation keys

- Volume control keys

#### Interface

- 2 x RJ45 10/100M Ethernet ports

- Power over Ethernet (IEEE 802.3af), class 1\*

- 1 x RJ9 (4P4C) handset port

- 1 x RJ9 (4P4C) headset port

#### Other Physical Features

- Color: Classic Grey

- Wall mountable

- External Yealink AC adapter

AC 100-240 V input and DC 5 V/0.6 A output

- Power consumption (PSU): 2-3 W

- Power consumption (PoE): 3-4 W

- Dimension (W x D x H x T):

188 x 189 x 162 x 50 mm

- Operating humidity: 10-95%

- Operating temperature: -10 to +45°C (+14 to

113°F)

- Storage temperature: -30 to +70°C (-22 to

+158°F)



## Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

## Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS

## DSCP

- SRTP for voice
- Transport Layer Security (TLS 1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Digest authentication
- OpenVPN, IEEE802.1X, L2TP VPN
- IPv6
- LLDP/CDP/DHCP VLAN
- ICE

- WPA2/WPA3

- Secure boot

- GARP (Generic Attribute Registration Protocol)

#### Package Features

- Package content:

- Yealink SIP-T31P IP phone

- Handset with handset cord

- Ethernet Cable (1.5m CAT5E UTP Cable)

- Stand (not applicable to US wall plate Standard)

- Quick Start Guide

- Power Adapter

- Qty/CTN: 10 PCS

- N.W/CTN: 9.79 kg

- G.W/CTN: 10.83 kg

- 

3	unit	<b>3.5mm Stereo Male Plug to 3 Pin XLR</b> <div>Distribution IEO c/o Ms. Rachel Kim L. Aure (STF-2025-01-00002) - 4</div>	4	0		4	Undelivered
---	------	--	---	---	--	---	-------------

#### Specification:

- Name: 3pin XLR Male to 3.5mm 1/8" TRS Male Cable
- Interface: XLR Male to 3.5mm 1/8" Male
- Cable Diameter: 4 mm
- Cable Conductor: 99.99% purity copper
- Insulation Material: PVC/PE
- 10 meters

4	unit	<b>Bluetooth Wireless Receiver</b> <div>Distribution IEO c/o Ms. Rachel Kim L. Aure (STF-2025-01-00002) - 3</div>	3	0		3	Undelivered
---	------	--	---	---	--	---	-------------

#### Specification:

- Bluetooth V5.1 Audio Adapter aptX
- 2RCA Wireless Music Adapter with 3.5mm to 2RCA

5	unit	<b>Computer Printer 3-in-1, Epson L3250</b> <b>Distribution</b> <i>NSTPO c/o Marlon V. Damplos (STF-2024-10-02396) - 1</i> <i>ULC c/o Maegan Lou A. Aruta (STF-2024-10-02472) - 1</i>	2	2	2025-09-01 #: CI-226524	0	Completed
---	------	--	---	---	----------------------------	---	-----------

**Specification:**

6	unit	<b>Computer Printer, All-in-One/Multifunction Colored-Ink Tank, Epson L5290</b> <b>Distribution</b> <i>CVM c/o Joel M. Israel (STF-2024-10-02394) - 3</i> <i>DMath c/o Genalyn M. Apas (STF-2024-10-02009) - 1</i> <i>LDHRAO c/o Jonathan Eduard S. Cabal (STF-2024-10-02526) - 1</i> <i>OUS c/o Antonleta Corazon D. Israel (STF-2024-12-03264) - 2</i>	7	7	2025-09-05 #: CI-226571	0	Completed
---	------	---	---	---	----------------------------	---	-----------

**Specification:**

- **Type:** All-in-One/Multifunction Colored-Ink Tank
- **Functions:** Print, Copy, Scan
- **Printing Technology:** Dye Ink
- **Print Resolution:** 5,760 x 1,440 DPI
- **Nozzle Configuration:** 180 Nozzles Black, 59 Nozzles per Color
- **Minimum Droplet Size:** 3 pl with Variable-Sized Droplet Technology
- **Ink Technology:** Dye Ink
- **Ultra-Low-Cost Printing:**
  - **Black:** Up to 4,500 pages
  - **Color:** Up to 7,500 pages
- **Ink Filling System:** Next-generation ink bottles for hassle and mess-free refills
- **Connectivity:**
  - **Wi-Fi**
  - **Wi-Fi Direct**
  - **Mobile Printing Apps**
- **Special Features:** Borderless photo printing

7	unit	<b>DSLR Camera Set, Canon EOS 1500D S18-55 III Kit</b> <b>Distribution</b> <i>DSO c/o Junard C. Gucela (STF-2024-10-02965) - 1</i>	1	0		1	Undelivered
---	------	--	---	---	--	---	-------------

**Specification:**

**Specifications:**

- **Sensor:** 18-megapixel APS-C-size CMOS sensor
- **Image Processor:** DIGIC 4+
- **Autofocus:** 9-point AF with 1 center cross-type AF point
- **ISO Range:** Standard ISO 100 - 6400 (expandable to 12800)

8	unit	<b>Data Cabinet, 9U, 9UHR-WMC-64099U</b> <b>Distribution</b> <i>CFES c/o Jesibel L. Muertigue (STF-2024-10-02589) - 1</i>	1	0		1	Undelivered
---	------	---	---	---	--	---	-------------

**Specification:**

**Features:**

- Solid construction
- Easy to install, no assembly required
- Compact design
- Includes one ceiling fan for cooling
- 2 removable side panels with key locks
- Top open brackets for cable and wire access
- Fits standard 19" rack-mount equipment
- Maximum rail depth: 13"
- Total usable space: 16" front to back

**Specifications:**

- **Color:** Black
- **Enclosure Material:** Steel
- **Weight:** 45 lbs
- **Dimensions:** 21.7" x 17.7" x 21.7" (L x W x H)
- **Thickness of Pillar:** 2mm
- **Thickness of Armored Glass:** 5mm
- **Rack U Height:** 9U

**Package Includes:**

- 1 x Network Cabinet
- 2 x Keys
- 1 x Screws Set

9	unit	<b>Desktop Computer</b> <div>Distribution DSO c/o Junard C. Gucela (STF-2024-10-02724) - 1</div>	1	0		1	Undelivered
---	------	---	---	---	--	---	-------------

**Specification:**

- **Processor:** Intel® Core™ i7-11700 or higher
- **Chipset:** Intel® H510 with ultra-durable capacitors
- **Graphics:** Intel® UHD Graphics 750
- **Memory:** At least 8GB Dual Channel, DDR4 at 3200MHz
- **Expansion Slots:**
  - 1 x M.2
  - 2 x PCI-e x1
  - 1 x PCI-e x16
- **SATA:** 4 x SATA 6Gb/s
- **Storage:** At least 250GB M.2 SSD
- **Operating System:** Genuine Windows 10 Home
- **Power Supply:** At least 500W Peak with ATX case
- **Monitor:** 24" LED IPS Full HD
- **Keyboard and Mouse**



10	unit	<b>Desktop Computer (Assembled)</b>  Distribution <i>SPO c/o Raizel M. Plamonte (STF-2024-10-02988) - 4</i> <i>ULC c/o Maegan Lou A. Aruta (STF-2024-10-02472) - 6</i>	10	0		10	Undelivered
----	------	--	----	---	--	----	-------------

**Specification:**

- **Processor:** Intel Core i5-11500 or higher
- **Motherboard:** Intel H510M S2H (6+2 Phases Digital VRM, Anti-sulfur resistors, LGA 1200, Micro-ATX, PCIe 4.0, USB 3.2 Gen) or higher
- **Memory:** 16GB (2x8) DDR4 or higher
- **SSD:** 500GB NVMe M.2 or higher
- **Optical Drive:** DVD-RW
- **Casing:** Includes 700W PSU
- **Monitor:** 23" IPS FHD
- **Operating System:** Genuine Windows 10 Home (OEM)
- **Peripherals:** Keyboard and mouse combo
- **Power Protection:** 500W IC controlled AVR
- **Audio:** Stereo speakers

11	set	<b>Desktop Computer (Assembled)</b>  Distribution <i>CoEd c/o Rublo B. Timkang (STF-2024-10-02753) - 2</i>	2	0		2	Undelivered
----	-----	---	---	---	--	---	-------------

**Specification:**

- **Processor:** Intel Core i3-11300 (4 cores / 8 threads) or higher
- **Motherboard:** Intel H510M Ultra Durable
  - Features: Gaming LAN, Anti-Sulfur Resistor, LGA-1200
- **Memory:** 8GB DDR4 2933 DIMM or higher
- **Storage:** 240GB NVMe SSD or higher
- **Keyboard and Mouse:** Combo
- **Casing:** With Power Supply
- **Monitor:**
  - Size: 18.5 inches
  - Resolution: HD Ready (1366 x 768)
  - Panel Type: TN
  - Connectivity Ports: 1 VGA Port, 1 HDMI Port
  - Aspect Ratio: 16:9
  - Brightness (Typical): 200 cd/m²
  - Refresh Rate: 60 Hz
- **Operating System:** Genuine Windows 10 Home (OEM)
- **AVR:** 500W IC controlled

12	unit	<b>Desktop Computer, All-In-One (AIO), 21.5" IPS, Lenovo A100</b>  Distribution <i>ULC c/o Maegan Lou A. Aruta (STF-2024-10-02472) - 10</i>	10	0		10	Undelivered
----	------	--	----	---	--	----	-------------

**Specification:**

- **Processor:** Intel Core i3-1005G1 (2 cores / 4 threads, 1.2 GHz base, up to 3.4 GHz, 4MB cache) or higher

- **Graphics:** Integrated Intel UHD Graphics
- **Chipset:** Intel SoC Platform
- **Memory:**
  - **Slot Configuration:** 1x 8GB SO-DIMM DDR4-3200
  - **Memory Slots:** Two DDR4 SO-DIMM slots, dual-channel capable
  - **Max Memory:** Up to 16GB DDR4-3200
- **Storage:** 512GB SSD M.2 2280 PCIe 3.0 NVMe
- **Display:** 21.5" FHD (1920x1080) IPS, 250 nits brightness
- **Touchscreen:** None
- **Keyboard:** Calliope Wireless Keyboard
- **Mouse:** Calliope Wireless Mouse
- **Expansion Slots:** Two M.2 slots (one for WLAN, one for SSD)
- **Ethernet:** Integrated 100/1000M
- **WLAN + Bluetooth:** 11ax, 2x2 + BT5.0
- **Rear Ports:**
  - 1x Power connector
  - 1x HDMI 1.4 out
  - 1x Ethernet (RJ-45)
  - 2x USB 2.0
  - 1x USB 3.1 Gen 1
- **Left Ports:**
  - 1x Headphone / Microphone combo jack (3.5mm)
  - 1x Card reader
  - 1x USB 3.1 Gen 1

13	sets	<b>Desktop Computer, Assembled</b>	1	0		1	<b>Undelivered</b>
Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02442) - 1							

**Specification:**

- **Processor:** Intel® Core i5 12th Gen with Intel® UHD Graphics 730 or higher
- **Motherboard:**
  - Intel® H610 Chipset for 12th Gen Intel® Core™ Series Processors
  - Dual Channel Non-ECC Unbuffered DDR4, 2 DIMMs
  - 6+1+1 Hybrid Digital VRM Design
  - Intel® GbE LAN
  - NVMe PCIe 3.0 x4 M.2
  - High Quality Audio Capacitors and Audio Noise Guard
  - mATX form factor or higher
- **RAM:** 16GB DDR4 3200 MHz or higher
- **Storage:**
  - SSD: 512GB NVMe PCIe Gen 3x4
  - HDD: 1TB 7200 RPM
- **Power Supply:** 650W 80 Plus Bronze Certified
- **Casing:** mATX casing with transparent acrylic side panel
- **Monitor:** 24" IPS, 72% NTSC color gamut with 75Hz refresh rate
- **Keyboard and Mouse Combo:**
  - Spill-resistant design

- Keyboard with up to 5 million keystrokes (excluding number lock key)
- Full-sized ambidextrous optical mouse
- **Operating System:** Genuine Windows 11

14	sets	<b>Desktop Computer, Assembled</b> Distribution _____ <i>DBM c/o Shellio G. Catorce (STF-2024-10-03023) - 1</i>	1	0		1	Undelivered
----	------	---	---	---	--	---	-------------

**Specification:**

- **Processor:** 12th Generation Intel® Core™ i5-12400 (2.50 GHz up to 4.40 GHz) or higher
- **Motherboard:** Intel® H610 Express Chipset Micro ATX
  - **VRM:** 6+1+1 Hybrid Digital VRM
  - **Features:** High quality capacitors and anti-sulfur resistors or higher
- **Operating System:** Genuine Windows 11 Home 64
- **Memory:** 8 GB DDR4-3200MHz (UDIMM) or higher
- **Graphics:** Integrated Graphics
- **SSD:** 256 GB SSD M.2 2280 PCIe or higher
- **Casing:** mATX casing
- **Power Supply:** At least 450W, True Rated 80+ Bronze
- **Monitor:**
  - **Size:** 24 inches
  - **Resolution:** FHD (1920 x 1080)
  - **Panel Type:** IPS
  - **NTSC Coverage:** 72%
  - **Response Time:** 5ms
  - **Refresh Rate:** 60Hz

15	unit	<b>Desktop Computer, Assembled, No OS with Monitor</b> Distribution _____ <i>DCST c/o Michael D. Dag-uman (STF-2024-10-02544) - 24</i>	24	0		24	Undelivered
----	------	--	----	---	--	----	-------------

**Specification:**

**Components:**

**Processor:**

- **Model:** Intel Core i3-13100
- **Cores/Threads:** 4 Cores / 8 Threads
- **Base Clock:** 3.40 GHz
- **Boost Clock:** Up to 4.50 GHz
- **Integrated Graphics:** Intel UHD Graphics 730 or higher

**Motherboard:**

- **Chipset:** Intel H610
- **Form Factor:** mATX
- **Memory Support:** Dual Channel Non-ECC Unbuffered DDR4, 2 DIMMs
-



**Features:**

- 6+1+1 Hybrid Digital VRM Design
- Intel GbE LAN
- NVMe PCIe 3.0 x4 M.2 Slot
- High Quality Audio Capacitors and Audio Noise Guard
- With D-Sub port

**RAM:**

- **Capacity:** 16GB DDR4
- **Speed:** 3200MHz or higher

**Storage:**

- **SSD:** 250 GB SATA III
- **Read Speeds:** Up to 550 MB/s or higher

**Casing and Power Supply:**

- **Casing:** Generic mATX
- **Power Supply Unit (PSU):** 700W

**Monitor:**

- Panel 21.45" (VA)
- Pixel Pitch (mm): 0.2493 (H) × 0.241 (V)
- Brightness (typical) 250 cd/m<sup>2</sup> or higher
- Contrast Ratio 3000 : 1 (Typical) 20 Million : 1 (DCR) or higher
- Response Time 4ms GtG or lower
- Optimum Resolution 1920 × 1080 @ 100Hz – HDMI, 1920 × 1080 @ 60Hz – VGA
- Display Colors 16.7 Million
- Signal Input VGA × 1, HDMI 1.4 × 1

16	pcs	<b>Desktop Monitor, Dell SE2425H</b>  Distribution AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1 ITEEM c/o Shaira B. Manapsal (STF-2024-10-02337) - 3	4	4	2025-09-05 #: CI-226571	0	Completed
----	-----	--	---	---	----------------------------	---	-----------

**Specification:**

- **Size:** 24" (23.8 inches) with narrow bezel
- **Resolution:** 1920 x 1080
- **Panel Type:** IPS
- **Aspect Ratio:** 16:9
- **Pixel Pitch:** 0.2745 x 0.2745 mm
- **Brightness:**
  - Minimum: 200 cd/m<sup>2</sup>
  - Typical: 250 cd/m<sup>2</sup>
- **Color Gamut:** NTSC 72% (CIE1931) (Typical)
- **Color Depth:** 16.7 million colors
- **Contrast Ratio:**
  - Minimum: 600:1
  - Typical: 1000:1



- **Response Time:** 5 ms (GtG at Faster)
- **Viewing Angle:** 178° (R/L), 178° (U/D) at CR?10
- **Surface Treatment:** Anti-glare
- **Connectivity:**
  - DSub
  - HDMI
- **HDMI Max Resolution:** 1920 x 1080 @ 75Hz

17	unit	Document Camera, Epson ELPDC21	1	1	2025-09-01 #: CI-226524	0	Completed
----	------	--------------------------------	---	---	----------------------------	---	-----------

**Specification:**

18	btls	<b>Epson 001 ink, Cyan, Genuine</b> <b>Distribution</b> <i>CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 10</i> <i>CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 5</i>	15	0	15	Undelivered
----	------	---	----	---	----	-------------

Specification:
----------------

None

19	btl's	<b>Epson 001 ink, Magenta, Genuine</b> <div> <b>Distribution</b>  CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 10  CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 5 </div>	15	0	15	Undelivered
----	-------	---	----	---	----	-------------

**Specification:**

None

20	btls	<b>Epson 001 ink, Yellow, Genuine</b> <div> <b>Distribution</b>  CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 10  CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 5 </div>	15	0		15	Undelivered
----	------	--	----	---	--	----	-------------

Specification:
----------------

None

21	unit	<b>External Hard Disk Drive (Portable, 1TB), USB 3.1, Adata</b> <div> <b>Distribution</b>  <i>ITEEM c/o Shaira B. Manapsal (STF-2024-10-02337) - 1</i> </div>	1	1	2025-09-01 #: CI-226524	0	Completed
----	------	--	---	---	----------------------------	---	-----------

**Specification:**

22	unit	<b>Graphics Processing Unit, Nvidia RTX 4060, Gigabyte</b>  <div> <b>Distribution</b>  <i>AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1</i> </div>	1	1	2025-08-29 #: CI-226480	0	Completed
----	------	---	---	---	----------------------------	---	-----------

[illegible]

23	pc	HDMI Cable, 15M	1	1	2025-09-01 #: CI-226524	0	Completed
		Distribution DSO c/o Junard C. Gucela (STF-2024-10-02965) - 1					

Specification:
----------------





- Symmetrical design suitable for left- and right-handed operation

33	pieces	<b>Mouse, Wired, Optical, USB, Rapoo</b> Distribution <i>CN c/o Guada Fe D. Amihan (STF-2024-10-02672) - 1</i>	1	0		1	Undelivered
----	--------	--	---	---	--	---	-------------

**Specification:**

- **Connectivity:** USB Port
- **Sensor:** Optical
- **DPI:** 1600
- **Work Method:** Wired
- **Buttons:** Left button, middle button, right button
- **Scroll Wheel:** Two-way
- **Design Highlights:**
  - Easy installation
  - 1600 DPI high-definition tracking engine
  - Anti-slip scroll wheel
  - Full-size, ambidextrous design

34	unit	<b>Portable printer, Canon Pixma TR150</b> Distribution <i>OUS c/o Antonieta Corazon D. Israel (STF-2024-12-03262) - 1</i>	1	0		1	Undelivered
----	------	--	---	---	--	---	-------------

**Specification:**

- **Print Speed (A4, ISO):** up to 9 / 5.5 ipm (mono/colour)
- **Wi-Fi, AirPrint, Mopria, Direct Wireless, Wireless PictBridge**
- **Borderless Printing (Top/Bottom/Left/Right margin: each 0 mm)**
- **1.44"/3.6 cm OLED Display (Monochrome)**

35	unit	<b>Power Supply for CPU, Ace Power</b> Distribution <i>UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03144) - 20</i>	20	0		20	Undelivered
----	------	--	----	---	--	----	-------------

**Specification:**

**SPECS:**

- **Compatible Devices:** Computer
- **Connector Type:** ATX
- **Output Wattage:** 800 Watts
- **Form Factor:** ATX
- **Wattage:** 800 watts
- **Cooling Method:** Air
- **Item dimensions:** L x W x H 5.5 x 5.91 x 3.4 inches
- 8 pins
- 6-7 SATA connectors

36	unit	<b>Printer, Tank Ink System, 3 in 1 (Print, Scan, Copy), Epson L3210</b> <div> Distribution  DSO c/o Junard C. Gucela (STF-2024-10-02965) - 1 </div>	1	0		1	Undelivered
----	------	---	---	---	--	---	-------------

**Specification:**
**Printer Specifications:**
**Printer Type:**

- Print, Scan, and Copy

**Tank Ink System:**

- Yes

**Scanner Type:**

- Flatbed Color Image Scanner

**Sensor Type:**

- CIS

**Optical Resolution:**

- 600 x 1200 dpi

**Copy Speed:**

- Maximum Copies from Standalone: 20 copies

**Maximum Copy Size:**

- A4, Letter

**ISO 29183 (A4 Simplex Flatbed):**

- Black: Up to 7.0 ipm
- Colour: Up to 1.7 ipm

**Maximum Copy Resolution:**

- 300 x 300 dpi

**Paper Handling:**

- Up to 20 Sheets Premium Glossy Photo Paper
- 10 Sheets Envelope
- 30 Sheets Postcard

**Output Capacity:**

- Up to 30 sheets

**Paper Input Capacity:**



- A4 Plain Paper: Up to 20 sheets
- Premium Glossy Photo Paper: Up to 20 sheets

**Maximum Paper Size:**

- 215.9 x 1200 mm (8.5 x 47.24")

**Nozzle Configuration:**

- 180 x 1 Nozzles Black
- 59 x 1 Nozzles per Colour (Cyan, Magenta, Yellow)

**Print Direction:**

- Bi-directional Printing

**Maximum Print Resolution:**

- 5760 x 1440 dpi (with Variable-Sized Droplet Technology)

**Minimum Ink Droplet Size:**

- 3 pl

37	pc	<b>Random Access Memory, DDR4, 3200Mhz, 8GB, Teamgroup</b> <div> Distribution  AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1 </div>	1	0		1	Undelivered
----	----	---	---	---	--	---	-------------

**Specification:**

- **Memory Capacity:** 8 GB
- **Speed:** 3200 MHz
- **Error Check:** Non-ECC
- **Module Type:** DIMM (For Desktop)
- **CAS Latency:** CL22
- **Form Factor:** DDR4
- **Pins:** 288 Pin
- **Memory Voltage:** 1.2 V
- **Compliance:** JEDEC compliant
- **Durability:** Guaranteed

38	pcs	<b>Solid State Drive, 500GB, 2.5" SATA, Samsung</b> <div> Distribution  AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1 </div>	1	0		1	Undelivered
----	-----	--	---	---	--	---	-------------

**Specification:**

- **Capacity:** 500 GB
- **Form Factor:** 2.5" SATA
- **Read Speed:** 560 MB/s
- **Write Speed:** 530 MB/s
- **Compatibility:** Suitable for both laptop and desktop

- **Warranty:** 5-year limited warranty

39	piece	<b>Solid State Drive, NVMe 1TB, Samsung</b> Distribution <i>AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1</i>	1	0		1	Undelivered
----	-------	--	---	---	--	---	-------------

**Specification:**

**SSD Specifications:**

- **Type:** Solid State Drive (SSD)
- **Interface:** NVMe M.2
- **Read Speed:** Up to 3500 MB/s
- **Write Speed:** Up to 3300 MB/s
- **TBW (Total Bytes Written):** Up to 1200 TBW
- **Features:**
  - Intelligent TurboWrite
  - Dynamic Thermal Guard
- **Interface:** PCIe Gen 3.0 x 4, NVMe 1.3
- **Memory Type:** V-NAND 3-bit MLC
- **Shock Resistance:** 1,500 G & 0.5 ms (Half sine)
- **Form Factor:** M.2 (2280)

40	pcs	<b>Solid State Drive, Teamgroup</b> Distribution <i>UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03144) - 10</i>	10	0		10	Undelivered
----	-----	---	----	---	--	----	-------------

**Specification:**

**SPECS:**

- Internal/External  
Internal
- Storage Capacity  
1TB
- Ports/ Interface  
SATA III
- SSD Form Factor  
2.5"
- 1 year warranty

41	unit	<b>UPS 800W ( for Computer), Wise Power</b> Distribution <i>CVM c/o Joel M. Israel (STF-2024-10-02394) - 4</i> <i>ULC c/o Maegan Lou A. Aruta (STF-2024-10-02472) - 2</i>	6	0		6	Undelivered
----	------	--	---	---	--	---	-------------

?Charging time: At most 4 hours

42	pcs	<b>USB DOCKING 6-IN-1 HUB</b>  <b>Distribution</b> <i>UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03150) - 5</i>	5	0		5	Undelivered
----	-----	---	---	---	--	---	-------------

**SPECS:**

- Number of interfaces: 7
- Interface type: USB 3.0
- Transmission rate: 5Gps
- Wire length: 1M

43	pcs	<b>USB Type Keyboard, Logitech K120</b>  <div> Distribution  UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03144) - 10 </div>	10	0		10	Undelivered
----	-----	---	----	---	--	----	-------------

- Cable length: atleast 150 cm
- Technical Specifications
- Keyboard
- Spill-resistant design 1Tested under limited conditions (maximum of 60 ml liquid spillage). Do not immerse the keyboard in liquid.
- 10-Key Number pad
- Caps lock indicator light
- Num lock indicator light
- Up to 10 million keystrokes (excludes number lock key)
- Key type: Deep profile
- Sustainability
- Black plastics: 51% post-consumer recycled material 2Excludes plastic in packaging.
- Product carbon footprint: 4.02 kg CO<sub>2</sub>e
- Certified carbon neutral
- USB type

44	pc	Wireless N Router (300Mbps) with 4-LAN Port, TP Link WR840N	1	0	1	Undelivered
		Distribution <i>DBM c/o Sheillo G. Catorce (STF-2024-10-03023) - 1</i>				

- **Wireless Transmission Rate:** 300 Mbps
- **Features:**
  - Ideal for both bandwidth-sensitive tasks and basic work
  - Easy wireless security encryption with a push of the WPS button



- IP-based bandwidth control to manage bandwidth allocation per PC
- WDS wireless bridge for seamless bridging and network expansion
- **Interface:**
  - 4 x 10/100 Mbps LAN Ports
  - 1 x 10/100 Mbps WAN Port
- **Buttons:** WPS/RESET Button
- **External Power Supply:** 9VDC / 0.6A
- **Wireless Standards:** IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

45	pcs	<b>XLR Connectors Female</b> Distribution <i>IEO c/o Ms. Rachel Kim L. Aure (STF-2025-01-00004) - 16</i>	16	0		16	Undelivered
----	-----	--	----	---	--	----	-------------

**Specification:**

- **Type:** Female 3-Pin XLR Connector
- **Number of Contacts:** 3
- **Mounting Type:** Cable mount
- **Body Orientation:** Straight
- **Contact Plating:** Silver
- **Housing Material:** Zinc
- **Termination Method:** Solder
- **Current Rating:** 16A
- **Voltage Rating:** 50V
- **Contact Material:** Bronze
- **Minimum Operating Temperature:** -30°C
- **Maximum Operating Temperature:** +80°C

46	pcs	<b>XLR Connectors Male</b> Distribution <i>IEO c/o Ms. Rachel Kim L. Aure (STF-2025-01-00004) - 16</i>	16	0		16	Undelivered
----	-----	--	----	---	--	----	-------------

**Specification:**

- **Type:** Male 3-Pin XLR Connector
- **Number of Contacts:** 3
- **Mounting Type:** Cable mount
- **Body Orientation:** Straight
- **Contact Plating:** Silver
- **Housing Material:** Nylon
- **Termination Method:** Solder
- **Current Rating:** 16A
- **Voltage Rating:** 50V
- **Contact Material:** Bronze
- **Minimum Operating Temperature:** -30°C
- **Maximum Operating Temperature:** +80°C

47	unit	<b>XLR Male to RCA Male</b> Distribution <i>IEO c/o Ms. Rachel Kim L. Aure (STF-2025-01-00002) - 5</i>	5	0		5	Undelivered
----	------	--	---	---	--	---	-------------



**Specification:**

- Item type:XLR to Dual RCA Audio Cable
- Interface: XLR Male to 2RCA
- Colour:black
- Material:Metal+woven mesh
- Size:Length: about 2 meters


**INSPECTION**

Date Inspected:


*21/8/20*☐ Inspected, verified and found in order  
as to quantity and specifications☐ Others: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

  
**JUDE B. ROLA**  
Inspector**ACCEPTANCE**

Date Recieved:

*21/8/20*☐ Complete☒ Partial  
**DOREEN B. ALBA**  
Head, Supply & Property Management