Republic of the Philippines

VISAYAS STATE UNIVERSITY

Visca, Baybay City, Leyte

SUPPLY & PROPERTY MANAGEMENT

1st 1AR

Supplier:

INSPECTION & ACCEPTANCE REPORT

ELECTROCOMPUTER DATA SYSTEM (EDS) IAR No:

R No: 25-09-1062

P.O No.: VSU-GOODS-25-25-176 (IGP)

Date: 2025-09-01

Office/Dept: Assorted Depts/Offices

50,800.00

Assorted PR's

No.	UNIT	DESCRIPTION	Quantity		Date		
			Per P.O	Actual	Received	Balance	Remarks
1		Camera Gimbal Stabilizer Built-in Al Tracker Upgrade Joystick Touch Screen for Mirrorless DSLR Camera, FELY TECH SCORP MINI 2 Handheld 3-Axis Gimbal Stabilizer Distribution EO c/o Marienne Joyce D. Gallego (IGP-2024-12-03252) - 1	1	1	2025-08-29 #: CI-226392	1 43 1	Completed

Specification:

Camera Gimbal Stabilizer Built-in Al Tracker Upgrade Joystick Touch Screen for Mirrorless DSLR Cameras

Specs:

- · Atleast, Integrated Underslung Handle, Super Weapon for Solo Filmmaking
- · Atleast, built for Mirrorless Cameras
- · Atleast, Quick-Release Design for Instant Vertical Filming Setup
- · Atleast, Smart Al for Intelligent Tracking
- · Atleast, Innovative Design, Super Weapon for Lone Filmaking
- · Atleast, Wireless Control and Easy to use
- · Atleast, 1.3" Touchscreen
- · Atleast, Electric Magic Knob and precise Control
- · Atleast, Enhanced Stability, Fearless of challenges
- Atleast, Explore Creative Freedom with Diverse Shooting Modes
 - Fish Follow Mode
 - o Pan and Tilt Follow
 - o Pan Follow
 - · FPV Follow
 - Lock Mode
- · Atleast, can connect to the App to unlock various functions
- · Atleast, Automatic Rotation, Time Lapse Photography and Panoramic Shooting

Specification:

Type: Bottom load water dispenser

Faucets:

Hot Water: Yes
Cold Water: Yes
Normal Water: Yes

Dispensing Control:

· Buttons: 3-Push Button control (Hot, Cold, Normal)

Safety Features:

- · Anti-scald Safety Lock Switch: Yes
- . Child Lock Safety Feature: Yes (on Hot Water Faucet)

Overflow Protection:

• Floater Indicator: Yes (prevents water overflow)

Capacity:

Hot Water: 1.2 Liters
Cold Water: 3.5 Liters

Power Rating:

Hot Water: 420 watts
Cold Water: 100 watts

Refrigerant: R134a

		Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS				
3	set	Distribution ODCCE c/o Mark Vincent G. Bonje (IGP-2024-10-02755) - 1	1	0	1	Undelivered

Specification:

- Frequency Response: 70 Hz-20 Khz
- · LF amplifier: 5 W/speaker
- Peak SPL (@1 meter): 100dB
- · LF Driver: 4.5" Kevlar
- · Kevlar woofer and low-mass silk-dome tweeter -
- · Input Impedance: 10 K ohms
- Power: 100-120V-50/60 Hz
- Monitor calibration
- 25W Class AB amplification per speaker

	:	Searces 1/4" TRS, unbalance 1/8" TS, RCA, and bare- 1/8" stereo headphone output Acoustic Space settings Acoustic Tuning controls let you flatten response for mit							
4	pc	Wall fan, TAILEE Distribution ODCCE c/o Mark Vincent G. Bonje (IGP-2024-10-02759) - 2	2	0		2	Undelivered		
		Blade Material: Metal Blade Size: 16 inches Speed Controller: Three-speed							
INSF	PECTI	ON .	ACC	EPTANCE			0.		
Date	Date Inspected: alim		Date	Recieved:	alily				
		Inspected, verified and found in order as to quantity and specifications		. 0	Complete				
		Others:			Partial				
				d					
JUDE B. ROLA Inspector			DOREEN B. ALBA Head, Supply & Property Management						