

Republic of the Philippines
VISAYAS STATE UNIVERSITY
Visca, Baybay City, Leyte
SUPPLY & PROPERTY MANAGEMENT

INSPECTION & ACCEPTANCE REPORT

Supplier: **NOLAS COMMERCIAL**
P.O No.: **PO-GF-MOOE-2025-05-0286**
Office/Dept: **ICTMC**

IAR No: 25-06-0753
Invoice No.: DR-11621/CI-004137
Date: 2025-06-25
40,180.00 GF-2025-01-00064

No.	UNIT	DESCRIPTION	Quantity		Date Received	Balance	Remarks
			Per P.O	Actual			
1	unit	Battery Tester/Analyzer	1	1	2025-06-24	0	Completed

Specification:

- Digital Analyzer Tester
- LCD display
- Type of measurement: CCA, IR, SoC and SOH
- Multi battery type: AGM, GEL, STD, Lead Acid,
- 12V/24V Battery
- 1 year warranty

2	unit	Battery, LiFePO4	2	0		2	Undelivered
---	------	------------------	---	---	--	---	-------------

Specification:

- 12 volts
- 20 Ah
- Nominal Capacity: 20ah 0.2 C
- Cycle Life:> 4000 Cycles at 0.2 ?; End-of-Life Capability
- Charging Voltage: 14.6±0.2V
- Charger Current: 4A
- Maximum Charging Current: 10.0
- Discharge Current: 4A
- Maximum Current Duration: 20A
- Discharge Cut-off Voltage: 10.0V
- Shell Material: ABS
- Size (L/Ft/H):180-200mm*75-80mm * 170-185mm

3	unit	Sealed Lead Acid Battery (VRLA)	4	4	2025-06-24	0	Completed
---	------	---------------------------------	---	---	------------	---	-----------

Offer:

12V

4	unit	Smart Battery Charger, 12V/24V, 25A/15A	2	0		2	Undelivered
---	------	---	---	---	--	---	-------------

Specification:

- Compatible type of battery: Lead Acid, AGM GEL, LiFePO4
- Intelligent Multiple Protection: Over heat protection, Overcurrent protection, electric shock protection, short circuit protection, reverse connect protection, overvoltage protection, Low voltage protection and fire protection.
- Multi Stage automatic charging: 1-Stage: Battery desulphation, 2-stage:Soft start charge, 3-stage: Bulk charge, 4-

stage: Absorption charge, 5-stage: Battery test, 6-stage: Recondition charge, Stage-7: Float & maintenance charging, 8-stage: Re-start charge after battery discharged.

- Input voltage: 100-240V AC, 50-60Hz
- Rated output: 12V 25A, 24V 15A
- Battery Range: 5-400Ah
- Compliant standards: CE, FCC, UKCA
- Colored Digital display indicator
- With Booster Mode
- US Plug type (AC)
- 1 year warranty

INSPECTION *ulash*

ACCEPTANCE *ulash*

Date Inspected:

Date Recieved:


☒ Inspected, verified and found in order
as to quantity and specifications

☐ Complete

☐ Others: _____

☒ Partial


JUDE B. ROLA
Inspector


VIVIAN V. BALBARINO
Head, Supply & Property Management