

INSPECTION & ACCEPTANCE REPORT

Assorted PR's

No.	UNIT	DESCRIPTION	Quantity		Date Received	Balance	Remarks
			Per P.O	Actual			
1	unit	4k Quantum Smart TV, DEVANT Distribution _____ <i>CFES c/o Jesibel L. Muertigue (STF-2024-10-02589) - 1</i>	1	1	2025-09-22 #: CI-226733	0	Completed
Specification:							
2	pc	Bottom Loading Water Dispenser, KAISA Distribution _____ <i>IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00004) - 1</i>	1	1	2025-10-29 #: CI 227103	0	Completed
Specification:							
• Product Model: JD-8044 • Voltage/Frequency: 220V ~ 50Hz • Cooling Power: 75W • Heating Power: ◦ Warm & Hot: Rated Power: 425W ◦ Cold & Hot: Rated Power: 500W • Heating Power: 425W • Carton Size: 355 x 325 x 1040 mm • Actual Product Size: 320 x 285 x 980 mm • Hot Water Temperature Range: 85 - 95°C							
3	unit	Coffee Maker, 12 Cups, IMARFLEX Distribution _____ <i>CN c/o Guada Fe D. Amihan (STF-2024-10-02662) - 1</i>	1	1	2025-09-22 #: CI-226733	0	Completed
Specification:							
4	pc	Heavy Duty Vacuum Cleaner, STANLEY Distribution _____ <i>CN c/o Guada Fe D. Amihan (STF-2024-10-02662) - 1</i>	1	1	2025-09-01 #: CI-226527	0	Completed
Specification:							

5	unit	Laminator Machine, A3, A3 OFFICOM Distribution <u>CAFS c/o Remenita J. Solis (STF-2024-10-02355) - 1</u>	1	1	2025-09-01 #: CI-226527	0	Completed
---	------	--	---	---	----------------------------	---	-----------

Specification:

6	unit	Smart TV Smart Quantum 4k, 55", DEVANT Distribution <u>AdO c/o Rubelyn P. Fernandez (STF-2024-10-02920) - 1</u>	1	1	2025-09-22 #: CI-226733	0	Completed
---	------	---	---	---	----------------------------	---	-----------

Specification:

7	set	Studio Monitors, 2-way active (Pair Left and Right Speaker), PRESONUS ERIS Distribution <u>NSTPO c/o Marlon V. Dampios (STF-2024-10-02464) - 1</u>	1	1	2025-10-29 #: CI 227103	0	Completed
---	-----	--	---	---	----------------------------	---	-----------

Specification:

- Frequency Response: 70 Hz-20 Khz
- LF amplifier: 5 W/speaker
- Peak SPL (@1 meter): 100dB
- LF Driver: 4.5" Kevlar
- Kevlar woofer and low-mass silk-dome tweeter
- Input Impedance: 10 K ohms
- Power: 100-120V-50/60 Hz
- Monitor calibration
- 25W Class AB amplification per speaker
- Balances 1/4" TRS, unbalance 1/8" TS, RCA, and bare-wire inputs
- 1/8" stereo headphone output
- Acoustic Space settings
- Acoustic Tuning controls let you flatten response for mixing accuracy

INSPECTION

ACCEPTANCE

Date Inspected:

10/30/25

Date Recieved:

10/30/25


☒ Inspected, verified and found in order as to quantity and specifications

☒ Complete

☐ Others: _____

☐ Partial


CLINT C. SARVIDA
Inspector


DOREEN B. ALBA
Head, Supply & Property Management