Republic of the Philippines

SO THE SOURCE STATE UNIVERSITY

Visca, Baybay City, Leyte

SUPPLY & PROPERTY MANAGEMENT

INSPECTION & ACCEPTANCE REPORT

Supplier:

ELECTROCOMPUTER DATA SYSTEM (EDS)

IAR No:

25-09-1079

P.O No.:

VSU-GOODS-25-26-214 (STF)

Date:

2025-09-02

Office/Dept: Assorted Depts/Offices

10 4 1055

1,907,166,50

Assorted PR's

NI-	UNIT	DESCRIPTION	Quantity		Date	Palance	Remarks
No. U	UNIT		Per P.O	Actual	Received	Balance	Remarks
1	unit	12" 500Watts Active Speaker System USB/ BLUETOOTH Function, includes Speaker wallmount, Kevler ZLX12D 12" Distribution DCST c/o Michael D. Dag-uman (STF-2024-10-02544) - 1	1	0		1:	Undelivered

- · 12" active speaker system
- Provide excellent vocal and bass performance
- · Rugged plastic mold design cabinet
- Bottom pole mount for tripod stand
- USB / Bluetooth Functions
- · Multiple handle for easy transport
- · 90 X 60 degrees wave guide horn for wide coverage
- · Multi angle enclosure can also use a monitor
- · Line level and direct mic input
- DSP management control w/ 5 preset settings Normal, DJ, Voice, Live, Flat
- System Type: 2 Way Bass Reflex
- LF: 12" woofer (2.5" Voice coil size)
- HF:1.7" Polymide Dome Tweeter
- Freq Response: 45Hz-20KHz
- Amp Power: 500W Class D
- · Input Impedance: 20K ohms
- Input Gain: line: +20dBu/Mic: +40dB
- Input Connector: Live (RCA & XLR combo jack)
- · Output Connector: Line (XLR loop through)
- THD: Less than 0.5%
- · LED Indicator: Power, Signal, Clip
- · Crossover Frequency: 2.5KHz
- AC Input: 220V 50-60Hz
- Speaker Stand Wall Mount Specs
 - Wall Mounting Speaker Pole

- Multi Angle Adjustability
- Foam Padded Speaker
- Base Plate Adjusts from 5.5" to 10.5"
- Rubberized Mounting Surface To Protect Your Speaker From Scratches
- o 35mm (1.38") Diameter Speaker Mount
- o Can Hold Speaker Up To 150 lbs (68.2kg)

		2 Line VOIP Phone, Yealink SIP-T31G				
2	unit	Distribution UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03144) - 2	2	0	2	Undelivered *

Specification:

(Must be compatible with existing fleet of VOIP Phone and Yeastar S300 Server)

1 Year Warranty

Audio Features

- · HD voice: HD handset, HD speaker
- · Smart Noise Filtering
- · Narrowband codec: PCMU (G.711A), PCMA

(G.711?), G.723.1, G.729, G.729A, G.729B,

G.729AB, G.726, iLBC

• DTMF: In-band, Out-of-band (RFC 2833) and SIP

INFO

- · Full-duplex hands-free speakerphone with AEC
- · VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- 2 VoIP accounts
- · Call hold, mute, DND
- · One-touch speed dial, hotline
- · Call forward, call waiting, call transfer
- · Group listening, SMS, emergency call
- · Redial, call return, auto answer
- · Local 5-way conferencing
- · Direct IP call without SIP proxy
- · Ring tone selection/import/delete

- Set date time manually or automatically
 Dial plan
 XML Browser, action URL/URI
 Integrated screenshots
- RTCP-XR, VQ-RTCPXR
- Enhanced DSS Key

Directory Commence of the Comm

- · Loal phonebook up to 1000 entries
- Black list
- XML/LDAP remote phonebook
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

IP-PBX Features

· Busy Lamp Field (BLF), Bridged Line Apperance

(BLA) A tupo alin hostan-best pat las una la

- · Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Flexible seating.
- · Call park, call pickup
- Executive and Assistant
- · Centralized call recording
- Visual voice mail
- Call recording

Display and Indicator

- 2.3" 132x64-pixel graphical LCD with backlight
- LED for call and message waiting indication
- · Dual-color (red or green) illuminated LEDs for

line status information

- · Intuitive user interface with icons and soft keys
- Multilingual user interface
- · Caller ID with name and number
- Power saving

Feature keys

- 2 line keys with LED
- 6 features keys: transfer, message, headset,

redial, mute, hands-free speakerphone

- 5 navigation keys
- Volume control keys

Interface The Description of the State of th

- 2 x RJ45 10/100M Ethernet ports
- Power over Ethernet (IEEE 802.3af), class 1*
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

Other Physical Features

- Color: Classic Grey
- Wall mountable
- External Yealink AC adapter

AC 100-240 V input and DC 5 V/0.6 A output

- Power consumption (PSU): 2-3 W
- Power consumption (PoE): 3-4 W
- Dimension (W x D x H x T):

188 x 189 x 162 x 50 mm

- · Operating humidity: 10-95%
- Operating temperature: -10 to +45°C (+14 to

113°F) LONDING AS FLEXIFIED MY INDUITED DO

- Storage temperature: -30 to +70°C (-22 to
- +158°F)

Management

- · Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- · Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- · Call server redundancy supported
- NAT traversal: STUN mode
- · Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- · Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS

DSCP

- SRTP for voice
 SRTP for voice
- Transport Layer Security (TLS 1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Digest authentication
- · OpenVPN, IEEE802.1X, L2TP VPN
- IPv6 DEMNIED AND ENDINE TO SELLENGE THE MEDICAL PROPERTY OF
- LLDP/CDP/DHCP VLAN
- · ICE

	WPA2	2/WPA3					
5.5	Secur	Le poot Le					
0	GARF	P (Generic Attribute Registration Protocol)					
	Packag	ge Features					
	Packa	age content:					
	- Yealin	nk SIP-T31P IP phone					
9		set with handset cord					
13		net Cable (1.5m CAT5E UTP Cable)					
8		d (not applicable to US wall plate Standard)					
8	- Quick	Start Guide			*		
	Power	er Adapter					
	2	TN: 10 PCS				W 27	
	1.55					V.1	
0	G.W/0	CTN: 9.79 kg					
0	G.W/0	CTN: 10.83 kg					
0	G.W/0	CTN: 10.83 kg	4	0		4	Undeliver
	G.W/C	3.5mm Stereo Male Plug to 3 Pin XLR	4	0		4	Undeliver
	unit	3.5mm Stereo Male Plug to 3 Pin XLR Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 4 cation: Name: 3pin XLR Male to 3.5mm 1/8" TRS Male Cable	4	0		4	Undeliver
	unit epecific	3.5mm Stereo Male Plug to 3 Pin XLR Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 4 cation:	4	0		4	Undeliver
	unit	3.5mm Stereo Male Plug to 3 Pin XLR Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00062) - 4 cation: Name: 3pin XLR Male to 3.5mm 1/8" TRS Male Cable Interface: XLR Male to 3.5mm 1/8" Male Cable Diameter: 4 mm Cable Conductor: 99.99% purity copper	4	0		4	Undeliver
	unit	3.5mm Stereo Male Plug to 3 Pin XLR Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 4 cation: Name: 3pin XLR Male to 3.5mm 1/8" TRS Male Cable Interface: XLR Male to 3.5mm 1/8" Male Cable Diameter: 4 mm	4	0		4	Undeliver
(9)	unit	3.5mm Stereo Male Plug to 3 Pin XLR Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 4 cation: Name: 3pin XLR Male to 3.5mm 1/8" TRS Male Cable Interface: XLR Male to 3.5mm 1/8" Male Cable Diameter: 4 mm Cable Conductor: 99.99% purity copper Insulation Material: PVC/PE	4	0		4	Undeliver
12	unit	3.5mm Stereo Male Plug to 3 Pin XLR Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 4 cation: Name: 3pin XLR Male to 3.5mm 1/8" TRS Male Cable Interface: XLR Male to 3.5mm 1/8" Male Cable Diameter: 4 mm Cable Conductor: 99.99% purity copper Insulation Material: PVC/PE 10 meters	3	0		3	
S	unit	3.5mm Stereo Male Plug to 3 Pin XLR Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 4 cation: Name: 3pin XLR Male to 3.5mm 1/8" TRS Male Cable Interface: XLR Male to 3.5mm 1/8" Male Cable Diameter: 4 mm Cable Conductor: 99.99% purity copper Insulation Material: PVC/PE 10 meters Bluetooth Wireless Receiver Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 3	3			3	
S	unit	3.5mm Stereo Male Plug to 3 Pin XLR Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 4 cation: Name: 3pin XLR Male to 3.5mm 1/8" TRS Male Cable Interface: XLR Male to 3.5mm 1/8" Male Cable Diameter: 4 mm Cable Conductor: 99.99% purity copper Insulation Material: PVC/PE 10 meters Bluetooth Wireless Receiver Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 3	3			3	Undeliver

(2)

		Computer Printer 3-in-1, Epson L3250			1		
5	unit	Distribution NSTPO c/o Marlon V. Damplos (STF-2024-10-02396) - 1 ULC c/o Maegan Lou A. Arufa (STF-2024-10-02472) - 1	2	2	2025-09-01 #: CI-226524	0	Completed
S	pecific	cation:					
	(8.4)	Printer Type: 3-in-1 (Print, Scan, Copy) Ink System: CIS (Continuous Ink Supply) filled with inks Design: Compact integrated tank		0			
		Features: High yield ink bottles Spill-free, error-free refilling					
		Connectivity: Wi-Fi, Wi-Fi Direct Borderless Printing: Up to 4R					
	elescu.	Computer Printer, All-in-One/Multifunction Colored-Ink Tank, Epson L5290					
5	unit	Distribution CVM c/o Joel M. Israel (STF-2024-10-02394) - 3 DMath c/o Genalyn M. Apas (STF-2024-10-02009) - 1 LDHRAO c/o Jonathan Eduard S. Cabal (STF-2024-10-02526) - 1 OUS c/o Antonieta Corazon D. Israel (STF-2024-12-03264) - 2	7	0		7 N1	Undelivere
		Type: All-in-One/Multifunction Colored-Ink Tank					
		Functions: Print, Copy, Scan					
	- 0.4	Printing Technology: Dye Ink Print Resolution: 5,760 x 1,440 DPI					
	-e d	Printing Technology: Dye Ink Print Resolution: 5,760 x 1,440 DPI Nozzle Configuration: 180 Nozzles Black, 59 Nozzles policy Minimum Droplet Size: 3 pl with Variable-Sized Droplet					
	- e d. - 174 - 124 - 126	Printing Technology: Dye Ink Print Resolution: 5,760 x 1,440 DPI Nozzle Configuration: 180 Nozzles Black, 59 Nozzles policy Minimum Droplet Size: 3 pl with Variable-Sized Droplet Ink Technology: Dye Ink Ultra-Low-Cost Printing: Black: Up to 4,500 pages		Y.			
	- 6 4.	Printing Technology: Dye Ink Print Resolution: 5,760 x 1,440 DPI Nozzle Configuration: 180 Nozzles Black, 59 Nozzles properties of the Minimum Droplet Size: 3 pl with Variable-Sized Droplet Ink Technology: Dye Ink Ultra-Low-Cost Printing: Black: Up to 4,500 pages Color: Up to 7,500 pages Ink Filling System: Next-generation ink bottles for hassle	Technology				
	- 6 4.	Printing Technology: Dye Ink Print Resolution: 5,760 x 1,440 DPI Nozzle Configuration: 180 Nozzles Black, 59 Nozzles po Minimum Droplet Size: 3 pl with Variable-Sized Droplet Ink Technology: Dye Ink Ultra-Low-Cost Printing: Black: Up to 4,500 pages Color: Up to 7,500 pages	Technology				
	- C - C - C - C - C - C - C - C - C - C	Printing Technology: Dye Ink Print Resolution: 5,760 x 1,440 DPI Nozzle Configuration: 180 Nozzles Black, 59 Nozzles po Minimum Droplet Size: 3 pl with Variable-Sized Droplet Ink Technology: Dye Ink Ultra-Low-Cost Printing: Black: Up to 4,500 pages Color: Up to 7,500 pages Ink Filling System: Next-generation ink bottles for hassle Connectivity: Wi-Fi	Technology				
	- C - C - C - C - C - C - C - C - C - C	Printing Technology: Dye Ink Print Resolution: 5,760 x 1,440 DPI Nozzle Configuration: 180 Nozzles Black, 59 Nozzles possible. Minimum Droplet Size: 3 pl with Variable-Sized Droplet Ink Technology: Dye Ink Ultra-Low-Cost Printing: Black: Up to 4,500 pages Color: Up to 7,500 pages Ink Filling System: Next-generation ink bottles for hasslet Connectivity: Wi-Fi Wi-Fi Direct Mobile Printing Apps	Technology			1	Undelivere

• Sensor: 18-megapixel APS-C-size CMOS sensor

	•	Image Processor: DIGIC 4+ Autofocus: 9-point AF with 1 center cross-type AF point ISO Range: Standard ISO 100 - 6400 (expandable to 12)					
8	unit	Data Cabinet, 9U, 9UHR-WMC-64099U Distribution CFES c/o Jesibel L. Muertique (STF-2024-10-02588) - 1	1	0		1	Undelivered
	Specific	cation:		<u></u>			nices solar
	Featur	Ellustooth Witnihas a Receiver					
			12				
		Solid construction					
		Easy to install, no assembly required				9	
		Compact design					
		Includes one ceiling fan for cooling					4
		2 removable side panels with key locks			(4		(3)
		Top open brackets for cable and wire access Fits standard 19" rack-mount equipment					
		Maximum rail depth: 13"					
		Total usable space: 16" front to back				10	
		ications: Affice o Mine Emilio 3 File XLR					
		Color: Black Enclosure Material: Steel					
		Weight: 45 lbs					
		Dimensions: 21.7" x 17.7" x 21.7" (L x W x H)					
		Thickness of Pillar: 2mm					
		Thickness of Armored Glass: 5mm					
		Rack U Height: 9U					
		ge Includes:					
61		- Velinous					
		1 x Network Cabinet					
		2 x Keys 1 x Screws Set					
	- 24-	1 x Screws Set	is .				
	-Epi	Desktop Computer					
9	unit	Distribution DSD c/o Junard C. Gucela (STF-2024-10-02724) - 1	1	0	Y I	1	Undelivered
	Specifi	cation:			and the second		
	1 b 70	Processor Intol® Coro IV i7 44709 or higher					
		Processor: Intel® Core™ i7-11700 or higher Chipset: Intel® H510 with ultra-durable capacitors					
		Graphics: Intel® UHD Graphics 750					
		Memory: At least 8GB Dual Channel, DDR4 at 3200MH	lz				
		Expansion Slots:	77 6				
		∘ 1 x M.2					
		° 2 x PCI-e x1					

o 1 x PCI-e x16

SATA: 4 x SATA 6Gb/s

Storage: At least 250GB M.2 SSD

Operating System: Genuine Windows 10 Home

Power Supply: At least 500W Peak with ATX case

Monitor: 24" LED IPS Full HD

Keyboard and Mouse

Desktop Computer (Assembled)

Distribution

SPO c/o Raizel M. Plamonte (STF-2024-10-02988) - 4

ULC c/o Maegan Lou A. Aruta (STF-2024-10-02472) - 6

Specification:

- Processor: Intel Core i5-11500 or higher
- Motherboard: Intel H510M S2H (6+2 Phases Digital VRM, Anti-sulfur resistors, LGA 1200, Micro-ATX, PCle 4.0, USB 3.2
 Gen) or higher
- . Memory: 16GB (2x8) DDR4 or higher
- SSD: 500GB NVMe M.2 or higher
- · Optical Drive: DVD-RW
- Casing: Includes 700W PSU
- Monitor: 23" IPS FHD
- Operating System: Genuine Windows 10 Home (OEM)
- Peripherals: Keyboard and mouse combo
- Power Protection: 500W IC controlled AVR
- Audio: Stereo speakers

	ghety	Desktop Computer (Assembled)				
11	set	Distribution CoEd c/o Rubio B. Timkang (STF-2024-10-02753) - 2	2	0	2	Undelivered

- Processor: Intel Core i3-11300 (4 cores / 8 threads) or higher
- · Motherboard: Intel H510M Ultra Durable
 - Features: Gaming LAN, Anti-Sulfur Resistor, LGA-1200
- Memory: 8GB DDR4 2933 DIMM or higher
- Storage: 240GB NVMe SSD or higher
- Keyboard and Mouse: Combo
- · Casing: With Power Supply
- · Monitor:
- O Size: 18.5 inches
- Resolution: HD Ready (1366 x 768)
- Panel Type: TN
 - Connectivity Ports: 1 VGA Port, 1 HDMI Port
 - o Aspect Ratio: 16:9
 - o Brightness (Typical): 200 cd/m²
 - o Refresh Rate: 60 Hz
- Operating System: Genuine Windows 10 Home (OEM)
- AVR: 500W IC controlled

12	unit	Desktop Computer, All-In-One (AIO), 21.5" IPS, Lenovo A100 Distribution ULC c/o Maegan Lou A. Aruta (STF-2024-10-02472) - 10	10	0	10	Undelivered
5	Specific	cation: upper cat				A-THER BOYCE
	100	Processor: Intel Core i3-1005G1 (2 cores / 4 threads, 1	GHz has	up to 3.4 GHz. 4	IMR cache) or highe	i i i i i i i i i i i i i i i i i i i
		Graphics: Integrated Intel UHD Graphics	COLIZ Dasi	e, up to 5.4 Of 12, 4	rivib cache) or highe	
		Chipset: Intel SoC Platform				
		Memory:				
		Slot Configuration: 1x 8GB SO-DIMM DDR4-32	nn			
		Memory Slots: Two DDR4 SO-DIMM slots, dual-		nable		
		Max Memory: Up to 16GB DDR4-3200	orianii oa	paolo		
		Storage: 512GB SSD M.2 2280 PCIe 3.0 NVMe				
		Display: 21.5" FHD (1920x1080) IPS, 250 nits brightness	I SIGNIEU			
		Touchscreen: None	2		*	
		Keyboard: Calliope Wireless Keyboard				
		Mouse: Calliope Wireless Mouse				
		Expansion Slots: Two M.2 slots (one for WLAN, one for	SSD)			
		Ethernet: Integrated 100/1000M				
		WLAN + Bluetooth: 11ax, 2x2 + BT5.0				
	•	Rear Ports:				
		o 1x Power connector				
		o 1x HDMI 1.4 out				
		o 1x Ethernet (RJ-45)				
		° 2x USB 2.0				
		o 1x USB 3.1 Gen 1				
**	•	Left Ports:		2		
		o 1x Headphone / Microphone combo jack (3.5mm)				
		o 1x Card reader				
		o 1x USB 3.1 Gen 1				
		Desktop Computer, Assembled				
13	sets	Distribution DBM c/o Sheilio G. Catorce (STF-2024-10-03023) - 1	1	0	1	Undelivered

- Processor: 12th Generation Intel® Core™ i5-12400 (2.50 GHz up to 4.40 GHz) or higher
- Motherboard: Intel® H610 Express Chipset Micro ATX
 - o VRM: 6+1+1 Hybrid Digital VRM
 - o Features: High quality capacitors and anti-sulfur resistors or higher
- Operating System: Genuine Windows 11 Home 64
- Memory: 8 GB DDR4-3200MHz (UDIMM) or higher
- . Graphics: Integrated Graphics
- SSD: 256 GB SSD M.2 2280 PCle or higher
- · Casing: mATX casing
- Power Supply: At least 450W, True Rated 80+ Bronze

		Separation 18 megapine APS-Dispe CMOS service					
		Monitor:					
		Size: 24 inches					
		 Resolution: FHD (1920 x 1080) 					
		Panel Type: IPS					
		NTSC Coverage: 72%					
		Response Time: 5ms					
		• Refresh Rate: 60Hz					
		Reflesh Rate. 00112					
		Desktop Computer, Assembled					
4	sets	Distribution Distribution	1	0		1	Undelivered
		NSTPO c/o Marion V. Dampios (STF-2024-10-02442) - 1					
Sp	ecific	cation:					
		Name and Interest Committee Committe		- 61-6			
		Processor: Intel® Core i5 12th Gen with Intel® UHD Gr	rapnics 730 c	or nigner			
	•	Motherboard:	2				
		 Intel® H610 Chipset for 12th Gen Intel® Core™ 		essors	34		
		 Dual Channel Non-ECC Unbuffered DDR4, 2 DI 	MMs				
		o 6+1+1 Hybrid Digital VRM Design					
		o Intel® GbE LAN					
		o NVMe PCle 3.0 x4 M.2				(12)	
		 High Quality Audio Capacitors and Audio Noise 	Guard				
		o mATX form factor or higher					
		RAM: 16GB DDR4 3200 MHz or higher					
		Storage: We blue College Party					
		o SSD: 512GB NVMe PCle Gen 3x4					
		 HDD: 1TB 7200 RPM 					
		Power Supply: 650W 80 Plus Bronze Certified					
		Casing: mATX casing with transparent acrylic side pane	ol.				
		Monitor: 24" IPS, 72% NTSC color gamut with 75Hz rei					
			resn rate				
	maig	Keyboard and Mouse Combo:					
		Spill-resistant design					
		 Keyboard with up to 5 million keystrokes (excluded) 	ing number l	ock key)			
		 Full-sized ambidextrous optical mouse 					
	•	Operating System: Genuine Windows 11					
T		Desktop Computer, Assembled, No OS with					
		Monitor management of the control	50 A0	20	- 1		
5	unit	Distribution	24	0	1	24	Undelivered
- 1		DCST c/o Michael D. Dag-uman (STF-2024-10-02544) - 24		9			
Sp	pecific	cation:					
- A		tak System: CIB (Comintous Int Timps) tilling with its					
С	ompo	onents: A thing 5-in-1 (Burn 2000 Color					
P	roces	sor:					
	-	Madely letal Core is 40400					
		Model: Intel Core i3-13100					
		Cores/Threads: 4 Cores / 8 Threads					
	•	Base Clock: 3.40 GHz					

- · Boost Clock: Up to 4.50 GHz
- · Integrated Graphics: Intel UHD Graphics 730 or higher

Motherboard:

- Chipset: Intel H610
- Form Factor: mATX
- . Memory Support: Dual Channel Non-ECC Unbuffered DDR4, 2 DIMMs
- · Features:
 - o 6+1+1 Hybrid Digital VRM Design
 - o Intel GbE LAN
 - O NVMe PCle 3.0 x4 M.2 Slot
 - High Quality Audio Capacitors and Audio Noise Guard
 - · With D-Sub port

RAM:

Capacity: 16GB DDR4
 Speed: 3200MHz or higher

Storage:

- . SSD: 250 GB SATA III
- . Read Speeds: Up to 550 MB/s or higher

Casing and Power Supply:

- Casing: Generic mATX
- Power Supply Unit (PSU): 700W

Monitor:

- Panel 21.45" (VA)
- Pixel Pitch (mm): 0.2493 (H) × 0.241 (V)
- · Brightness (typical) 250 cd/m² or higher
- Contrast Ratio 3000: 1 (Typical) 20 Million: 1 (DCR) or higher
- Response Time 4ms GtG or lower
- Optimum Resolution 1920 × 1080 @ 100Hz HDMI, 1920 × 1080 @ 60Hz VGA
- Display Colors 16.7 Million
- Signal Input VGA × 1, HDMI 1.4 × 1

		Desktop Monitor, Dell SE2425H				
16	pcs	Distribution AdC c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1 ITEEM c/o Shaira B. Manapsai (STF-2024-10-02337) - 3	4 .	0	4	Undelivered

- Size: 24" (23.8 inches) with narrow bezel
- Resolution: 1920 x 1080
- Panel Type: IPS
- Aspect Ratio: 16:9
- Pixel Pitch: 0.2745 x 0.2745 mm
- Brightness

		 Minimum: 200 cd/m² 					
		o Typical: 250 cd/m²					
		Color Gamut: NTSC 72% (CIE1931) (Typical)					
		Color Depth: 16.7 million colors					
		Contrast Ratio:					
		o Minimum: 600:1					
		○ Typical: 1000:1					
	bac 1	Response Time: 5 ms (GtG at Faster)					
		Viewing Angle: 178° (R/L), 178° (U/D) at CR?10					
		Surface Treatment: Anti-glare					
	•	Connectivity:					
		o DSUB					
		∘ HDMI					
	•	HDMI Max Resolution: 1920 x 1080 @ 75Hz					(3)
		Document Camera, Epson ELPDC21		_			
	unit	Distribution	1	1	2025-09-01	0	Completed
		LDHRAO c/o Jonathan Eduard S. Cabal (STF-2024-10-02526) -			#: CI-226524	(*	
3		Pixels: 2MP (1920 x 1080 pixels)					
	Speci	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Optical Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p)					
	Speci	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Optical Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p)					
	ghac	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Optical Zoom: 12x Frame-Per-Second (FPS): 30					
	ghac	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Optical Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p) Built-in Microphone: Yes AV Recording: Yes					
	2000	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Doptical Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p) Built-in Microphone: Yes AV Recording: Yes Epson 001 ink, Cyan, Genuine	,	0		45	Hadeliness
	ghac	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Digital Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p) Built-in Microphone: Yes AV Recording: Yes	15	0		15	Undelivered
3	btls	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Digital Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p) Built-in Microphone: Yes AV Recording: Yes Epson 001 ink, Cyan, Genuine Distribution CAC do Niffa C. Gofredo (STF-2024-10-02350) - 10	15	0		15	Undelivered
S	btls	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Optical Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p) Built-in Microphone: Yes AV Recording: Yes Epson 001 ink, Cyan, Genuine Distribution CAC c/o Niffa C. Gofredo (STF-2024-10-02350) - 10 CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 5	15	0		15	Undelivered
3	btls	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Optical Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p) Built-in Microphone: Yes AV Recording: Yes Epson 001 ink, Cyan, Genuine Distribution CAC c/o Niffa C. Gofredo (STF-2024-10-02350) - 10 CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 5	15	0		15	Undelivered
S	btls	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Digital Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p) Built-in Microphone: Yes AV Recording: Yes Epson 001 ink, Cyan, Genuine Distribution CAC clo Niffa C. Gofredo (STF-2024-10-02350) - 10 CAC clo Niffa C. Gofredo (STF-2024-10-02350) - 5 cation:	15	0		15	Undelivered
S	btls	Pixels: 2MP (1920 x 1080 pixels) Camera Sensor: 1/2.7 inch CMOS Sensor Resolution: Up to Full HD (1080p) Zoom: Digital Zoom: 10x Digital Zoom: 12x Frame-Per-Second (FPS): 30 Output Resolution: Up to Full HD (1080p) Built-in Microphone: Yes AV Recording: Yes Epson 001 ink, Cyan, Genuine Distribution CAC c/o Niffs C. Gofredo (STF-2024-10-02350) - 10 CAC c/o Niffs C. Gofredo (STF-2024-10-02360) - 5 Cation:		0			Undelivered

	-	Epson 001 ink, Yellow, Genuine					
20	btls	Distribution CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 10 CAC c/o Niffa C. Gofredo (STF-2024-10-02360) - 5	15	0		15	Undelivered
5	Specific	cation:					
	None	Supply Garantee Line , Authorize throught					
21	unit	External Hard Disk Drive (Portable, 1TB), USB 3.1, Adata Distribution ITEEM Co Shaira B. Manapsal (STF-2024-10-02337) - 1	1	1	2025-09-01 #: CI-226524	0	Completed
	Specific	cation:	_				
		Type: Portable Capacity: 1TB Interface: USB 3.1 (Max. 5 Gb/s) Texture: Plastic/Rubber Operating Voltage: DC 5V, 900mA		ni yai	4		
		System Requirements: O Windows XP / Vista / 7 / 8 / 8.1 / 10 Mac OS X 10.6 or later Linux Kernel 2.6 or later Additional Features: Shock-absorbing				¥	
22	unit	Graphics Processing Unit, Nvidia RTX 4060, Gigabyte	1	1	2025-08-29 #: CI-226480	0	Completed
2)		AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1					
	- Annaly	cation:	31	17		7	mqdyAdlaa
		CUDA Cores: 3072 Base Clock: 1.83 GHz					
. 4			RELEVEN				
	ana	Memory Speed: 17 Gbps					
		Standard Memory Config: 8GB					
		Memory Interface Width: 128-bit GDDR6					ic apos-10 bus
		Memory Bandwidth: 272 GB/sec					
	10	PCLE: 40					
		Technology Support:					
		 Ray Tracing Cores: 3rd Generation 					
		 Tensor Cores: 4th Generation NVIDIA Architecture: Ada Lovelace NVIDIA DLSS: 3 	EPTAR				8
		HDMI Cable, 15M	program				
23	рс	Distribution DSO c/o Junard C. Gucela (STF-2024-10-02965) - 1	ENTIAE	KBU1.	2025-09-01 #: CI-226524	0	Completed
	1	1 // consist the least the constant of the con		1			

27 ur	High Quality Pure Copper Gold-plated 19-pin HDMI connectors Oxygen-free copper cable PVC jacket with high visibility nylon braiding Laptop 14", MSI 1298PH Distribution CAFS c/o Remenita J. Solis (STF-2024-10-02352) - 1 cification:	1	0	1	Undelivered
	 Gold-plated 19-pin HDMI connectors Oxygen-free copper cable PVC jacket with high visibility nylon braiding 		0	3	i. militared
Spec	 Length: 20 meters Type: HDMI Male to HDMI Male Transfer Speed: Up to 10.2 Gbps Construction: 				
26 pc	UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03144) -	2	0	2	Undelivered
	HDMI to HDMI Cable 3 meters Distribution DBS c/o Alma Gofredo (STF-2024-11-03194) - 14 Diffication: HDMI to HDMI Cable 3 meters	14	0	14	Undelivered
111	cification: MI Cable, rubberized/heavy-duty; 15m length; gold-plated c	onnectors; full	copper with ether	met; version: at leas	it 2.0; high-speed
24 p	HDMI Cable, rubberized/heavy-duty; 15m length; gold-plated connectors; full copper with ethernet Distribution CET c/o Michelle A. Borleo (STF-2024-10-02137) - 3	3	0	3	Undelivered
- 00 - 10 - 10 - 10 - 10	Connector Type: HDMI Length: 15 meters Bandwidth: 10.2 Gbit/s Resolution: 4K x 2K @ 60Hz 4K x 2K @ 30Hz 1080P 3D Material: Pure Copper Shielding: 4 standard protective layers to shield interference. Features: No delay, no flashing screen, stable picture	erence			•

 Memory: 4GB RAM, 1 x SO-DIMM socket (for expansion) Display: 14.0" (16:9) LED-backlit FHD (1920x1080), 60Hz, Anti-Glare Panel, 45% NTSC Video Processor: NVIDIA GeForce MX330, 2GB GDDR5 VRAM Storage: 512GB PCle Gen3 x2 SSD Laptop 15", Lenovo 151RHS 2025-09-01 1 0 Completed 28 1 sets Distribution #: CI-226524 DSO c/o Junard C. Gucela (STF-2024-10-02965) - 1 Specification: . Display Size: 15.6" IPS, Full HD . Processor: Intel® Core™ i7 12th Gen Processor Memory: 8GB RAM Storage: 256 GB NVMe PCle SSD · Battery: Lithium polymer 60 Wh (rated capacity) · Connectivity: WLAN: IEEE 802.11a/b/g/n/ac/ax (2.4 GHz and 5 GHz, 2 × 2 MIMO, WPA / WPA2 / WPA3) Bluetooth: Bluetooth 5.1 · Ports: USB-C × 1 (supports data, charging, and DisplayPort) USB-C × 1 (supports data and charging) USB 3.2 Gen 1 × 1 USB 2.0 x 1 o HDMI × 1 3.5 mm headset and microphone 2-in-1 jack × 1 . Keyboard: Full-size Backlit Keyboard + Numeric Keypad Camera: 1080P FHD Camera · Audio: Microphone × 4; Speakers × 2 Power Adapter: 65 W USB-C Power Adapter · Charger Cable: USB-C Charger Cable · Extras: Free Backpack Memory, DDR4 (16GB), Teamgroup 0 1 29 Undelivered pc 1 Distribution AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1 Specification: ?2x8GB 2400Mhz DDR4 ?Non-ECC CL15 DIMM ?Desktop Memory RAM with heat spreaders Microphone Wire, 1 Spool 2 0 2 Undelivered 30 spool Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 2 Specification: · Type: Stereo Microphone Wire · Length: 100m spool Cable thickness: approx. 0.8 cm

· Durable, flexible design eliminates kinks and twists · High fidelity transmission · Heavy duty Low impedance Low noise Oxygen free Microphone, Wired, Cardioid, Shure SM58-CN 31 unit 0 Undelivered . 4 IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 4 Specification: · Frequency response tailored for vocals, with brightened midrange and bass rolloff . Uniform cardioid pickup pattern isolates the main sound source and minimizes background noise Pneumatic shock-mount system cuts down handling noise · Effective, built-in spherical wind and pop filter Supplied with break-resistant stand adapter which rotates 180 degrees · Cardioid (unidirectional) dynamic Frequency response: 50 to 15,000 Hz Mouse (USB Type), Logitech B100 32 pcs 10 0 10 Undelivered . UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03144) -Specification: · Wired mouse with right and left click buttons and a scroll wheel · Optical sensor with 1000 dpi resolution for precise and flowing cursor control . 5.9' long integrated USB cable · Connects to any computer via the USB connection Striking blue light on sides and scroll wheel Rubber side surfaces and rubber scroll wheel offer improved grip · Symmetrical design suitable for left- and right-handed operation Mouse, Wired, Optical, USB, Rapoo 33 0 1 Undelivered pieces Distribution CN c/o Guada Fe D. Amihan (STF-2024-10-02672) - 1 Specification: · Connectivity: USB Port · Sensor: Optical • DPI: 1600 Work Method: Wired . Buttons: Left button, middle button, right button Scroll Wheel: Two-way Design Highlights:
 | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Design Highlights: | Easy installation o 1600 DPI high-definition tracking engine · Anti-slip scroll wheel

		Full-size, ambidextrous design				Secretary and the second
34	unit	Portable printer, Canon Pixma TR150 Distribution OUS c/o Antonieta Corazon D. Israel (STF-2024-12-03262) - 1	1	0	1	Undelivered
5	Specific	cation: The Brahaman on with arrestile				
		Print Speed (A4, ISO): up to 9 / 5.5 ipm (mono/colour) Wi-Fi, AirPrint, Mopria, Direct Wireless, Wireless PictBri Borderless Printing (Top/Bottom/Left/Right margin: each 1.44"/3.6 cm OLED Display (Monochrome)				
35	unit	Power Supply for CPU, Ace Power Distribution UR c/o Jannet Lealie Evelyn S. Codog (STF-2024-11-03144) - 20	20	0	20	Undelivered
5	Specific	cation:				
	SPECS	Compatible Devices: Computer Connector Type: ATX Output Wattage: 800 Watts Form Factor: ATX Wattage: 800 watts			î t	
	le sile	Cooling Method: Air Item dimensions: L x W x H 5.5 x 5.91 x 3.4 inches 8 pins 6-7 SATA connectors				
36	unit	Printer, Tank Ink System, 3 in 1 (Print, Scan, Copy), Epson L3210 Distribution DSO c/o Junard C. Gucela (STF-2024-10-02965) - 1	1,	0	1	Undelivered
5	Specific	cation:		Lancon politica integration	-	-
	Printer	r Specifications:				
	Printer	r Type:				
		Print, Scan, and Copy				
	Tank I	nk System:	•			
	Holi-	Yes				
	Scann	er Type:				
		Flatbed Color Image Scanner				
		or Type: Light of the deposition of the terms of the term				

• CIS

Optical Resolution:

• 600 x 1200 dpi

Copy Speed: A September 100 with particular

Maximum Copies from Standalone: 20 copies

Maximum Copy Size:

A4, Letter

ISO 29183 (A4 Simplex Flatbed):

Black: Up to 7.0 ipm

. Colour: Up to 1.7 ipm

Maximum Copy Resolution:

300 x 300 dpi

Paper Handling:

- · Up to 20 Sheets Premium Glossy Photo Paper
- 10 Sheets Envelope
 - 30 Sheets Postcard

Output Capacity:

· Up to 30 sheets

Paper Input Capacity:

- · A4 Plain Paper: Up to 20 sheets
- Premium Glossy Photo Paper: Up to 20 sheets

Maximum Paper Size:

215.9 x 1200 mm (8.5 x 47.24")

Nozzle Configuration:

- 180 x 1 Nozzles Black
- 59 x 1 Nozzles per Colour (Cyan, Magenta, Yellow)

Print Direction:

Bi-directional Printing

Maximum Print Resolution:

5760 x 1440 dpi (with Variable-Sized Droplet Technology)

Minimum Ink Droplet Size:

		3 pl ujouranii			*		
37	рс	Random Access Memory, DDR4, 3200Mhz, 8GB, Teamgroup Distribution AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1	1	0		1	Undelivered
S	pecific	cation:		-			
	- Cally - Exec - Sano - Year - Cally	Memory Capacity: 8 GB Speed: 3200 MHz Error Check: Non-ECC Module Type: DIMM (For Desktop) CAS Latency: CL22 Form Factor: DDR4 Pins: 288 Pin Memory Voltage: 1.2 V					æ
		Compliance: JEDEC compliant Durability: Guaranteed					
38	pcs	Solid State Drive, 500GB, 2.5" SATA, Samsung Distribution AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1	1	0		1	Undelivered
₽	- CHILL - CHILL - EXP	Capacity: 500 GB Form Factor: 2.5" SATA Read Speed: 560 MB/s Write Speed: 530 MB/s Compatibility: Suitable for both laptop and desktop Warranty: 5-year limited warranty					
39	piece	Solid State Drive, NVMe 1TB, Samsung Distribution AdO c/o Rubelyn P. Fernandez (STF-2024-10-02919) - 1	1	0		1	Undelivered
	Specifi	cation:					
	- Brest - Brest - Brest	Type: Solid State Drive (SSD) Interface: NVMe M.2 Read Speed: Up to 3500 MB/s Write Speed: Up to 3300 MB/s TBW (Total Bytes Written): Up to 1200 TBW Features: • Intelligent TurboWrite			50		

		USB Type Keyboard, Logitech K120					
3	pcs	Distribution UR c/o Jannet Leslie Evelyn S. Codog (STF-2024-11-03144) - 10	10	0	2	10	Undelivered
5	pecifi	eation: TVENTERALIAM VER	поля в У	34115		-	
			4				
	•	Cable length: atleast 150 cm		OFFER			
		Technical Specifications					
		Keyboard Spill-resistant design 1Tested under limited conditions (maximum of	60 ml liquid en	illaga) Do na	t immerse	the keyboard is
		liquid.	naximum or	ou mi ilquid sp	maye). Do no	t irriirrier se	the keyboard ii
	06D4	10-Key Number pad 05.331.703.5					The Line of the
		Caps lock indicator light					
		Num lock indicator light					- 3-
	gita S	Up to 10 million keystrokes (excludes number lock key)			28.10		
	•	Key type: Deep profile		elayă malent	E gyrtaA et		
		Sustainability					
		Black plastics: 51% post-consumer recycled material 2E	xcludes plas	tic in packagin	g.	Jimpanii	
		Product carbon footprint: 4.02 kg CO2e					
		Certified carbon neutral					
	•	USB type	£.			The second	Ny Denis
		Wireless N Router (300Mbps) with 4-LAN Port,			NEXSVE TOXALS	se ovileu	
		TP Link WR840N	1	municipal of the	He literary intolly	ove Con	Maria III
32	I		1	1 1)		1 1	Undelivered
14	рс	Distribution		Immedia m	leab blamak	ald ben	- Citacity Gree
4	рс	DBM c/o Shellio G. Catorce (STF-2024-10-03023) - 1	·		laub thum alv mirnof murum	nilq ben	E Y
		A DESCRIPTION OF THE PROPERTY			de muit desi materi terang eth Functions	nilq ben	2
	pecifi	DBM c/o Shellio G. Catorce (STF-2024-10-03023) - 1 cation:			control desi control term con Functions de on easy to	nilq ben	
	Specifi •	DBM c/o Shellio G. Catorce (STF-2024-10-03023) - 1 cation: Wireless Transmission Rate: 300 Mbps		braue to	ore says and	and beginned the state of the s	
	Specifi •	DBM c/o Shellio G. Catorce (STF-2024-10-03023) - 1 cation: Wireless Transmission Rate: 300 Mbps Features:	Charles of	bratia te respi si na mend gu ranna an noch	menseres par ne seres par ne seres par ne seres par necessaries n	mity ben- plessed to mad along spets to a a magnity in	
	Specifi •	DBM c/o Shellio G. Catorce (STF-2024-10-03023) - 1 cation: Wireless Transmission Rate: 300 Mbps	ic work	braue is	CENTURE TO SERVING TO SERVING	nity ben ploy not please it is mad along spelp tid it is night it one term of	
	Specifi •	Cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base	ic work the WPS but	tton	Matana Trada M year po eff Mg avan me Mg esuzolah M tahi lathia M Kuting Matah	iniq pen alesta (in anad al., if spelo (id x e nighte it restaure)	
	Specifi •	Cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of	ic work the WPS but	tton per PC	CUY FUNCTIONS TO THE SERVE TO THE PROPERTY OF	mility mega- micro medical in a micro dia in a spelo tidi in se tanno di septitalia spettalia	
	specifi •	cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth	ic work the WPS but	tton per PC ansion	Matana Trada M year po eff Mg avan me Mg esuzolah M tahi lathia M Kuting Matah	iniq pen inication to made to a spelo trial en inputa it rectorial engal rec- local se	
	specifi •	Cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth WDS wireless bridge for seamless bridging and Interface: 4 x 10/100 Mbps LAN Ports	ic work the WPS but	tton per PC ansion	Carry Cancerons The corrections The corrections The correction of the correction The correction of the correct	Most re- please to a med alore spelo tid x a might it ce term a agritum loov 'S' alore 'T'	
	specifi •	Cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth WDS wireless bridge for seamless bridging and Interface: 4 x 10/100 Mbps LAN Ports 1 x 10/100 Mbps WAN Port	ic work the WPS but	tton per PC ansion	CHY FUNCTIONS TO THE SERVE THE THE THE THE THE THE THE THE THE TH	side per side side side side side side side side	
	specifi •	Cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth WDS wireless bridge for seamless bridging and Interface: 4 x 10/100 Mbps LAN Ports 1 x 10/100 Mbps WAN Port Buttons: WPS/RESET Button	ic work the WPS but	tton per PC ansion	cury Functions provided the property of the provided that in the provided that in the provided that in the provided the p	Most re- please to a pelo un x	
	specifi •	Cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth WDS wireless bridge for seamless bridging and Interface: 4 x 10/100 Mbps LAN Ports 1 x 10/100 Mbps WAN Port Buttons: WPS/RESET Button External Power Supply: 9VDC / 0.6A	ic work the WPS but th allocation network expa	tton per PC ansion	Company of the compan	Most re- Mos	
	specifi •	Cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth WDS wireless bridge for seamless bridging and Interface: 4 x 10/100 Mbps LAN Ports 1 x 10/100 Mbps WAN Port Buttons: WPS/RESET Button	ic work the WPS but th allocation network expa	tton per PC ansion	A CONTRACTOR	Most re- Mos	
	specifi •	Cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth WDS wireless bridge for seamless bridging and Interface: 4 x 10/100 Mbps LAN Ports 1 x 10/100 Mbps WAN Port Buttons: WPS/RESET Button External Power Supply: 9VDC / 0.6A	ic work the WPS but th allocation network expa	tton per PC ansion	CONTRACTOR CONTRA	Most re- Mos	
	specifi •	cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth WDS wireless bridge for seamless bridging and Interface: 4 x 10/100 Mbps LAN Ports 1 x 10/100 Mbps WAN Port Buttons: WPS/RESET Button External Power Supply: 9VDC / 0.6A Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE	ic work the WPS but th allocation network expa	tton per PC ansion	Company of the compan	Most re- please to a please to	
•	specifi.	Cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth WDS wireless bridge for seamless bridging and Interface: 4 x 10/100 Mbps LAN Ports 1 x 10/100 Mbps WAN Port Buttons: WPS/RESET Button External Power Supply: 9VDC / 0.6A Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE	ic work the WPS but th allocation network expans	tton per PC ansion	CONTRACTOR CONTRA	side per selection of the selection of t	
5	pcs	cation: Wireless Transmission Rate: 300 Mbps Features: Ideal for both bandwidth-sensitive tasks and base Easy wireless security encryption with a push of IP-based bandwidth control to manage bandwidth WDS wireless bridge for seamless bridging and Interface: 4 x 10/100 Mbps LAN Ports 1 x 10/100 Mbps WAN Port Buttons: WPS/RESET Button External Power Supply: 9VDC / 0.6A Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE XLR Connectors Female	ic work the WPS but th allocation network expans	tton per PC ansion	CONTRACTOR CONTRA	Most re- please to a please to	

		Voltage Rating: 50V	n veneza o	latinis.		
	•	Contact Material: Bronze Minimum Operating Temperature: -30°C Maximum Operating Temperature: +80°C XLR Connectors Male	Selection of a	graph Sport Control	Her	
46	pcs	Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00004) - 16	16	0	16	Undelivered
28	•	Housing Material: Nylon Termination Method: Solder Current Rating: 16A Voltage Rating: 50V Contact Material: Bronze Minimum Operating Temperature: -30°C Maximum Operating Temperature: +80°C				
47	unit	XLR Male to RCA Male Distribution IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00002) - 5	5	0	5	Undelivered
\$		Item type:XLR to Dual RCA Audio Cable Interface: XLR Male to 2RCA Colour:black Material:Metal+woven mesh Size:Length: about 2 meters		PRESE 2		
INSF	ECTIO		ACCE	PTANCE	are tarried or prop-	
		Desktop Computer, All-In-Oea (AIO), 21, 71-198, Lenevo A160 Lenevo A1			40	

Date Recieved:				
Complete				
Partial				
^				
L M				
Supply & Property Management				