

Republic of the Philippines
VISAYAS STATE UNIVERSITY
Visca, Baybay City, Leyte
SUPPLY & PROPERTY MANAGEMENT

INSPECTION & ACCEPTANCE REPORT

Supplier: **LEYTE PAPERWORLD**
P.O No.: **VSU-GOODS-25-44-397 (STF)**
Office/Dept: **Assorted Depts/Offices**

IAR No: 25-11-1582
Date: 2025-11-18
163,230.00 Assorted PR's

No.	UNIT	DESCRIPTION	Quantity		Date Received	Balance	Remarks
			Per P.O	Actual			
1	unit	Aircon Split Type (1.5 HP), PANASONIC CS-XPU12WKQ Distribution CVM c/o Joel M. Israel (STF-2024-10-02414) - 1 IEO c/o Ma. Rachel Kim L. Aure (STF-2025-01-00120) - 1	2	2	2025-11-17 #: DR 23043	0	Completed

Specification:

AIRCON SPLIT TYPE 1.5 HP

Weight

- Net weight:
 - Indoor - 8 kg
 - Outdoor - 23 kg
- Gross weight:
 - Indoor - 9 kg
 - Outdoor - 30 kg

Dimensions

- Net Dimensions (W x H x D):
 - Indoor - 779mm x 290mm x 209mm
 - Outdoor - 780mm x 542mm x 289mm
- Gross Dimensions (W x H x D):
 - Indoor - 861mm x 364mm x 255mm
 - Outdoor - 891mm x 603mm x 396mm

Power Requirements:

- 230 V

Power Consumption:

- 750 W

General Specifications

- Remote: Yes
- Timer: Yes
- Cooling Capacity: 11,020 kj/h
- Control Type: With remote
- Cooling Area (sq. meters): Survey is recommended
- Noise Level (Indoor) – Low: 28dB
- Filter: Yes
- Airflow Direction Control (Up & Down): Automatic
- Airflow Direction Control (Left & Right): Manual
- Temperature Control: With remote
- Fan Speed: 5 Speed Level
- Energy Efficiency Ratio: 14.69

2	unit	Audio Amplifier Two Channels, NEW BAXS CS3000 Distribution NSTPO c/o Marlon V. Dampios (STF-2024-10-02488) - 1	1	1	2025-11-17 #: DR 23043	0	Completed
---	------	---	---	---	---------------------------	---	-----------

Specification:

- **Stereo Output Power:**
 - 8?: 650W x 2
 - 4?: 1100W x 2
- **Total Harmonic Distortion:** <0.01%
- **Signal-to-Noise Ratio:** >105 dB
- **Input Impedance:**
 - Balanced: 20K?
 - Unbalanced: 10K?
- **Input Sensitivity:** 0 dB / 1V
- **Voltage Gain:** Adjustable, maximum 32 dB (40 times)
- **Frequency Response:** 20 Hz–20 kHz ±0.15 dB
- **Conversion Rate:** 50V/μs
- **Channel Isolation:**
 - 105 dB at 1 kHz
 - 80 dB at 20 kHz
- **Damping Coefficient:** 80/1 kHz > 250
- **Connector Types:**
 - Input: XLR female, TRS (1/4 inch)
 - Output: Speaker socket
- **Indicator Lights:** Signal indicator, protection indicator, overheat protection, overload protection
- **AC Input Voltage:** AC220V / 50-60 Hz

3	unit	Computer Monitor, LG27UL550-W Distribution FMO c/o Glen Agnes Baroro (STF-2025-05-00676) - 1	1	0		1	Undelivered
---	------	---	---	---	--	---	-------------

Specification:

- **Size:** 27 inches

- Resolution: 3840 x 2160 (4K)
- Panel Type: IPS
- Aspect Ratio: 16:9
- Pixel Pitch: 0.1554 x 0.1554 mm
- Brightness (Typ.): 300 cd/m²
- Color Gamut (Typ.): sRGB 98% (CIE1931)
- Color Depth: 1.07 billion colors
- Contrast Ratio (Min.): 700:1
- Contrast Ratio (Typ.): 1000:1
- Response Time: 5ms (GtG at Faster)
- Viewing Angle: 178° (R/L), 178° (U/D)
- Surface Treatment: Anti-Glare

4	unit	Microwave oven, SHARP R-20A(S) Distribution DFST c/o Pearl P. Vistal (STF-2024-10-02910) - 1	1	1	2025-11-17 #: DR 23043	0	Completed
---	------	--	---	---	---------------------------	---	-----------

Specification:

- AC Line Voltage: 230 V, 60 Hz single phase
- Distribution Line Fuse/Circuit Breaker: 10 A
- AC Power Required:
 - Microwave: 1270 W
- Output Power:
 - Microwave: 800 W (IEC 60705)
 - Off Mode (Energy Save Mode): Less than 1.0 W
- Microwave Frequency: 2450 MHz (Group 2/Class B)
- Outside Dimensions (W x D x H): 439.5 x 338.2 x 256.2 mm
- Cavity Dimensions (W x D x H): 306.0 x 306.6 x 208.2 mm
- Oven Capacity: 20 litres
- Turntable Size: 255 mm
- Weight: Approx. 10.9 kg
- Oven Lamp: 25 W/230 V
- Control: Mechanical
- Timer: 35 minutes
- Power Levels: 5
- Door Opening: Push

5	pieces	Stainless Steel Ceiling Fan, ASAHI C56SS Distribution ULC c/o Maegan Lou A. Aruta (STF-2024-10-02480) - 6	6	6	2025-11-17 #: DR 23043	0	Completed
---	--------	---	---	---	---------------------------	---	-----------

Specification:

Specifications:

- Blade Size: 56 inches (1,400 mm)
- Blade Type: 3-leaf stainless steel propeller
- Power Consumption: 90 W
- Speed Settings: 3 speeds
- Max Speed: 350 RPM

- **Max Airflow:** 270 m³/min
- **Control:** Wall-mounted continuous rotary switch
- **Safety Feature:** Equipped with resettable Thermal Cut-Off Fuse (TCO)
- **Dimensions:** 140 x 140 x 58 cm (L x W x H)

INSPECTION		ACCEPTANCE	
Date Inspected: 11/18/25		Date Recieved: 11/18/25	
☒ Inspected, verified and found in order as to quantity and specifications ☐ Others: _____ _____ _____		☐ Complete ☒ Partial	
 CLINT C. SARVIDA Inspector		 DOREEN B. ALBA Head, Supply & Property Management	