



Republic of the Philippines
VISAYAS STATE UNIVERSITY
 Visca, Baybay City, Leyte

PURCHASE REQUEST

PPMP No. : **PPMP-2024-081524-0352**PR No.: **STF-2024-09-01653**Date: **09-05-2024**Dept./Office: **PPO**Category: **Construction
and Electrical Supplies**Section/End-User: **Mario C. Bantugan**Project Title/Code: **College of Nursing**Funding Source: **Special Trust Fund**

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	(PB-1) - Panel board dead front three phase pure copper busbar 100 amperes MCCB center main 3 phase with grounding terminal bolt-on type 20 KAIC	unit	1	60,000.00		60,000.00
Specification: 2- 15AT/50AF, 2P,15KAIC,MCB - 5- 20AT/50AF, 2P,15KAIC,MCB - 5- 30AT/50AF, 2P,15KAIC,MCB - 4- 40AT/50AF, 2P,15KAIC,MCB -						
2	(PB-2)- Panel board dead front three phase pure copper busbar 60 amperes MCCB single phase side mai	unit	1	15,000.00		15,000.00
Specification: Branches : • 1- 15AT/50AF, 2P,15KAIC,MCB • 2- 20AT/50AF, 2P,15KAIC,MCB • 2- 30AT/50AF, 2P,15KAIC,MCB						
3	(PB) -Panel board dead front three phase pure copper busbar 80 amperes MCCB 3 phase center main wit	set	2	50,000.00		100,000.00
Specification: • 2-15AT/50AF, 2P, 15KAIC, MCB • 6-20AT/50AF, 2P, 15KAIC, MCB • 6-30AT/50AF, 2P, 15KAIC, MCB						
4	0.60m x 0.60m Floor Tiles - White	pcs	900	210.00		189,000.00
Specification:						

- Size: 0.60m x 0.60m
- Color: White
- Type: Floor Tiles
- Thickness: At least 10mm
- Material: Ceramic

5	Coco Lumber, 2" x 6" x 12'	pcs	500	350.00		175,000.00
6	Concrete Hollow Blocks (CHB), 4"	pieces	217	25.00		5,425.00

Specification:

- Type: 3-Cell Concrete Hollow Block
- Size: 4 inches
- Strength: At least 350 psi
- Standard Size: Typical industry dimensions for a 4" CHB

7	D-1: 0.9mx2.1m swing door w/ smoked glass and analok frame	unit	1	9,030.00		9,030.00
8	D-2: 0.8mx2.1m flush door on 2"x6" wooden jamb	unit	1	11,600.00		11,600.00
9	D-3: 2.387mx2.1m sliding glass door on aluminum frame	unit	1	24,000.00		24,000.00
10	D-4: 0.8mx2.1m panel door on 2"x6" wooden jamb	unit	1	8,400.00		8,400.00
11	Electrical Aircon Outlet, 1 gang (flush type)	set	5	250.00		1,250.00
12	Electrical Outlet, Single gang universal outlet with ground, (surface type)	pcs	16	100.00		1,600.00

Specification:

- Current Rating: 10A
- Voltage Rating: 250V
- Features:
 - Universal design
 - Includes ground
 - Durable construction
 - Heavy duty
- Type: Surface mount

13	Electrical PVC Conduit 20 mm diameter	length	275	100.00		27,500.00
14	Electrical PVC Conduit with coupling, 50 mm. dia	length	50	300.00		15,000.00
15	Electrical PVC Conduit with coupling, 63 mm. dia.	length	30	400.00		12,000.00
16	Electrical Square Box (PVC), 6" x 6"	pcs	6	200.00		1,200.00

Specification:

PVC Square Box 6"x 6"

17	Electrical Square Box (PVC), 4" x 4"	pcs	2	150.00		300.00
----	--------------------------------------	-----	---	--------	--	--------

18	Electrical Switch, 2-gang, Flush type	pcs	10	200.00		2,000.00
19	Electrical Switch, 3-way, flush type	pcs	5	200.00		1,000.00
Specification: • Heavy duty • Good quality						
20	Electrical Switch, Single (Flush type)	set	13	150.00		1,950.00
21	Electrical Tape, Vinyl	rolls	30	75.00		2,250.00
Specification: • Material: Flexible PVC with aggressive rubber adhesive • Features: ◦ Flame retardant ◦ Compatible with plastic cable and wire harness insulations ◦ Primary electrical insulation for wire and cable splices rated up to 600 volts • Dimensions: 19mm width x 16mm length x 0.155mm thickness • Type: Heavy Duty • Certification: ASTM approved						
22	Electrical Wire, THHN / THWN, AWG 10 (5.5mm ²), Stranded, 150 meters/box	boxes	5	8,500.00		42,500.00
Specification: • Type: THHN/THWN, Building Wire • Gauge: AWG 10 (5.5mm²) • Stranding: Stranded with Nylon Insulation • Length: 150 meters/box • Certification: UL listed						
23	Electrical Wire, THHN AWG 1/19(38mm ²) Stranded Copper for 600volts	meter	150	250.00		37,500.00
24	Electrical Wire, THHN/THWN, AWG 2 (30 mm ²), Stranded	meters	10	400.00		4,000.00
Specification: • Type: THHN/THWN, Building Wire • Gauge: AWG 2 (30 mm²) • Stranding: Stranded with Nylon Insulation • Certification: UL listed						
25	Electrical Wire, THHN/THWN, AWG 6 (14 mm ²), Stranded Wire 600 volts, 150 meters per roll	rolls	1	18,000.00		18,000.00
26	Electrical Wire, THHN/THWN, AWG 8 (8mm ²), Stranded, 150 meters/box	boxes	2	9,750.00		19,500.00
Specification:						

- **Type:** THHN/THWN, Building Wire
- **Gauge:** AWG 8 (8mm²)
- **Stranding:** Stranded with Nylon Insulation
- **Length:** 150 meters/box
- **Certification:** UL listed

27	Electrical, 2 gang convenience outlet, (surface type) universal	pcs	2	70.00		140.00
----	---	-----	---	-------	--	--------

Specification:

Specifications:

- **Type:** 2 gang convenience outlet
- **Mounting:** Surface type
- **Compatibility:** Universal

28	Electrical, Junction box with cover, 4" x 4"	pcs	130	50.00		6,500.00
----	--	-----	-----	-------	--	----------

Specification:

Specifications:

- **Material:** Electrical PVC
- **Color:** Orange
- **Heat Resistant:** Yes
- **Waterproof:** Yes
- **Certification:** UL certified

29	Electrical, Utility Box, 2" x 4", Orange	piece	27	30.00		810.00
----	--	-------	----	-------	--	--------

Specification:

PVC

30	Electrical, Utility Box, 2" x 4"(Surface Type)	pcs	20	40.00		800.00
----	--	-----	----	-------	--	--------

31	Emergency Light, 2 x 3 Watts	pcs	16	2,500.00		40,000.00
----	------------------------------	-----	----	----------	--	-----------

Specification:

- **Power:** 2 x 3 Watts
- **Quality:** Good quality, durable
- **Features:**
 - Dome reflector for wider light distribution
 - Automatic operation (turns on instantly when power is cut off)
 - Equipped with overcharging protection
 - Fuse protected
- **Illumination:** Illuminates areas more than 1 lux
- **Light Source:** 2 x 1W High Power SMT LED
- **Battery:**
 - 4V 4.0Ah - 6V 4.5Ah Sealed Lead Acid
- **Charging Time:** <20 hours

• Performance Time: 26 hours (at full charge)						
32	Fire Alarm Bell 6" dia., 24V DC	piece	5	1,072.00		5,360.00
33	Fire Alarm Control Panel 5 Zone	set	1	34,970.00		34,970.00
Specification: • Type: Fire Alarm Control Panel • Zones: 5 Zones • Loops: 5 Loops • Input Power: 220VAC, 60Hz • Auxiliary Power (Battery): DC 24V 300mAH (Ni-Cd Battery) • Charging Voltage/Current: DC 29V, 60mA • Loop Voltage/Current: ◦ Normal: DC 24V ◦ Short-Circuit: 5V, Under 30mA • Exterior Resistance: Round-trip under 50? • Amount of Smoke Detectors: Max. 20 per loop • Amount of Heat Detectors: No limit (except electronic types) • End of Line Resistance: 10K? • Output Current for Indicating Lamp: Max. 120mA • Output Current for Alarm Bell: Max. 120mA						
34	Heat Detector Alarm System	unit	2	2,200.00		4,400.00
Specification: • Type: Heat Detector Alarm System • Wiring: Two wires conventional, 24V DC • Operating Voltage: 9V to 35V DC • Alarm Current: 40 - 50mA • Alarm Indication: Red LED ON • Temperature Range: -10°C to +50°C • Standby Current: 50?A • Humidity Range: <95% Relative Humidity • Detecting Range: 50 sq. m @ 6-12 m installation height • Standard/Certification: EN54-5, UL521, GB4716-2005 • Dimensions: 100 mm diameter x 46 mm height						
35	Illuminated Entrance Sign	pcs	2	18,000.00		36,000.00
36	Illuminated exit sign	pcs	3	550.00		1,650.00
37	LED Slim Round down light 9 watts indoor recessed type daylight	set	8	400.00		3,200.00
38	Louver Housing with 18 watts T8 LED tube surface mount, Troffer fixture, rush proof single lights, 4	set	10	1,200.00		12,000.00
39	Louver Housing with LED Fluorescent Lamp(2 x 36W), Surface Type	set	30	1,200.00		36,000.00
40	Miscellaneous	lot	2	10,000.00		20,000.00
41	Miscellaneous/Consumables	lot	1	10,000.00		10,000.00
42	Modern Ceiling Lights Square LED Panel Acrylic Diameter	set	2	2,500.00		5,000.00

43	Nails, Common Wire, 1-1/2"	kl	20	90.00		1,800.00
44	Neon Strip Lights Outdoor type Warm white 220VAC 7Watts	meters	20	200.00		4,000.00
45	Orbit Fan, 405 mm diameter, 220 volts	unit	4	2,500.00		10,000.00

Specification:

- Diameter: 405 mm
- Voltage: 220 volts
- Features:
 - Durable, high-performance motor
 - 4-speed remote switch
 - Thermal fuse protection

46	Paint, Semi Gloss Latex, Good Quality	gal	10	950.00		9,500.00
47	Sand, Washed	cu.m.	2	1,500.00		3,000.00
48	Screened Sand	cu.m.	5	1,500.00		7,500.00
49	Semi Gloss Enamel white	gallon	38	900.00		34,200.00
50	Sheets, (G.I.) Corrugated, Gauge 26 (0.40mm), 8'	piece	40	550.00		22,000.00

Specification:

Standard width

51	Smoke Detector Alarm System	unit	20	1,400.00		28,000.00
----	-----------------------------	------	----	----------	--	-----------

Specification:

- Type: Smoke Detector Alarm System
- Wiring: Two wires conventional, 24V DC
- Operating Voltage: 9V to 35V DC
- Alarm Current: 40mA @ 24V
- Alarm Indication: Red LED ON
- Temperature Range: -10°C to +50°C
- Standby Current: 55mA
- Humidity Range: 0% to 95%
- Relative Humidity: Non-condensing
- Alarm Output: Remote LED
- Sensitivity: 0.15 dB/m
- Standard/Certification: EN54-7 & UL268
- Dimensions: 100 mm diameter x 46 mm height

52	Smoked fixed glass partition with analok frame	sq.m.	10	4,550.00		45,500.00
53	Square Box 5x5ln (PVC) high quality	pcs	3	100.00		300.00
54	Tex Screw, Metal, 2"	pcs	1000	5.00		5,000.00
55	Thermoplastic fixture (TF) wire, #16AWG 1.25mm, single one	roll	7	3,000.00		21,000.00
56	W- Clip	pcs	2000	10.00		20,000.00
57	W-1: 4.15mx1.76m sliding glass window on analok frame	unit	1	3,500.00		3,500.00

58	W-2: 2.69mx1.48m fixed glass on analok frame	unit	2	10,700.00		21,400.00
59	W-3: 2.0mx1.2m sliding glass window on analok frame	unit	1	10,000.00		10,000.00
	TOTAL					1,248,535.00

Purpose: Repair for Nursing

Checked by:  CLINT C. SARVIDA		Funds Available:  ALICIA M. FLORES <i>UNIFAST</i>	
TWG - Construction and Electrical Supplies		HEAD, BUDGET OFFICE	
Signature:	Prepared by:  MARIO C. BANTUGAN	Noted by:  MARLON G. BURLAS	Approved by:  PROSE IVY G. YEPES
Printed Name:			
Designation:		UNIT HEAD, PROJECT LEADER	PRESIDENT, VSU