



Republic of the Philippines

VISAYAS STATE UNIVERSITY

Visca, Baybay City, Leyte

PURCHASE REQUEST

PPMP No.: 131-5-1544-2023-7-0-2

PR No.: GF-2022-12-02469

Date: 12-19-2022

Dept./Office: MMDC

Category: IT Supplies and

in and

Section/End-User: Windy O. Tuyan

Equipment

Project Title/Code: UNIVERSITY INTEGRATED

INFORMATION OFFICE-2023

Funding Source: General Fund - MOOE

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1 1	External Hard Disk Drive (Portable, 1TB), USB 3.1	unit	3	3,500.00		10,500.00

Specification:

?Shock-absorbing

?Interface: USB 3.1 (Max.5Gb/s)

?Capacity: 1TB

?Texture: Plastic/Rubber

?Operating Voltage: DC 5V, 900mA

?System Requirements: Windows XP / Vista / 7 / 8 / 8.1 / 10, Mac OS X 10.6 or later, Linux Kernel 2.6 or later

2	HDMI to HDMI cable	piece	10	500.00	5,000.00
	Specification:				
	?chord 1.8 meter long				
3	Ink, Epson 003,Genuine Black 65mL	btl	3	350.00	1,050.00
4	Power supply for Panasonic camcorder	рс	2	1,700.00	3,400.00

Specification:

- · Brand:Panasonic
- · Model: SAE0011
- Color classification: black original Panasonic 12V3A white original Panasonic 12V3A

5	Power supply LED Video Light	pc	1	2,000.00	2,000.00
0	Fower supply LED video Light	PC	1	2,000.00	2,000.00

Specification:

- DC 15V Switch Power Supply Adapter
- Input Voltage: AC100V-240V
- Output Voltage: DC 15V
- · Output Current: 6A
- Output Adaptor Jack size: 5.5mm x 2.5-2.1mm Compatible

	 Shell Material: Plastic 								
	D	T T							
5	Power Supply, 300 watts, ATX w/ ATXcasing	pieces	1	1,200.00	1,200.0				
	SD Card, 128 GB	pcs	4	1,500.00	6,000.0				
	Specification:								
	?Memory SD Card- 128 GB UHS-I SDX	С							
	?Card Type: SDXC								
	?Storage Capacity: 128GB								
	?Bus type: UHS-1								
	?Data Transfer Read Speed: 170 MB/s	Maximum	(Burst)						
	?Write speed: 90 MB/s maximum (Burst		,						
	?Write speed: 30 MB/s Minimum	*							
	?Built-in Write Protect Switch								
	?Durability: Shockproof, Temperature E	xtremes,	waterproof, X-ra	Proof					
	?Opening Temperature: -25 to 85C		•	0.00					
100									
}	Tweeter Driver Unit	pcs	2	1,900.00	3,800.0				
	Specification:								
	 Compression Driver Unit 								
	 Power: 400 Watts 								
	 Power: 400 Watts Impedance: 8 Ohms 								
	• Impedance: 8 Ohms								
	Impedance: 8 OhmsSensitivity: 106 dB / W / M	z							
	• Impedance: 8 Ohms	z							
	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH 	z							
-	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter		2	300.00	600.0				
	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters	z	2	300.00	600.0				
	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter		2	300.00	600.0				
	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: 		2	300.00	600.0				
	Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable	unit	2						
	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: 		2	1,500.00					
	Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable	unit							
	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: 	unit	1	1,500.00					
	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: USB 3.0 HUB, 7 Ports, High Specification: 	unit unit	1 g Power USB H	1,500.00	1,500.0				
	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: USB 3.0 HUB, 7 Ports, High Specification: USB 3.0 HUB, 7 Ports, High Specification: Up to 5Gbps Super-Speed, High 	unit unit	1 g Power USB H	1,500.00	1,500.0				
	Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: USB 3.0 HUB, 7 Ports, High Specification: Up to 5Gbps Super-Speed, High Support 2TB large capacity HDD	unit unit	1 g Power USB H	1,500.00	1,500.0				
	 Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: USB 3.0 HUB, 7 Ports, High Specification: Up to 5Gbps Super-Speed, High Support 2TB large capacity HDD Plug and Play, No driver require 	unit unit eed Strong	1 g Power USB H 30Mbps, Full Sp	1,500.00	1,500.0				
	Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: USB 3.0 HUB, 7 Ports, High Specification: USB 3.0 HUB, 7 Ports, High Specification: Plug and Play, No driver require compatible with windows series,	unit unit eed Strong speed 48	1 g Power USB H 30Mbps, Full Sp	1,500.00	1,500.0				
	Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: USB 3.0 HUB, 7 Ports, High Specification: Up to 5Gbps Super-Speed, High Support 2TB large capacity HDE Plug and Play, No driver require compatible with windows series, Interface independent switch decenters.	unit unit eed Strong speed 48	1 g Power USB H 30Mbps, Full Sp	1,500.00	1,500.0				
	Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: USB 3.0 HUB, 7 Ports, High Specification: USB 3.0 HUB, 7 Ports, High Specification: Plug and Play, No driver require compatible with windows series,	unit unit eed Strong speed 48	1 g Power USB H 30Mbps, Full Sp	1,500.00	1,500.0				
0	Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: USB 3.0 HUB, 7 Ports, High Specification: Up to 5Gbps Super-Speed, High Support 2TB large capacity HDE Plug and Play, No driver require compatible with windows series, Interface independent switch decenters.	unit unit unit unit unit eed Strong speed 48	1 g Power USB F 80Mbps, Full Sp Linux,	1,500.00 IUB 3.0 peed 12Mbps, and Low Speed 1.5Ml	1,500.0				
	Impedance: 8 Ohms Sensitivity: 106 dB / W / M Freq. Response: 1.5kHz ~ 20kH Voice Coil: ?51.5mm Magnet: 134 x 15mm Universal HDMI to VGA Adapter Cable, at least 1.8 meters Specification: Universal HDMI to VGA Adapter Cable USB 3.0 Hub, 7 Ports Specification: USB 3.0 HUB, 7 Ports, High Speed Up to 5Gbps Super-Speed, High Support 2TB large capacity HDD Plug and Play, No driver require compatible with windows series, Interface independent switch deserted.	unit unit eed Strong speed 48	1 g Power USB H 30Mbps, Full Sp	1,500.00	6,000.0				

Transmission Type: 2.4GHzPolar Pattern: Omnidirectional

• Frequency Response: 20Hz-20KHz (±3dB)

• Distortion: ?0.1%

· Sampling Rates: 48kHz

· Bit Depth: 16Bit

· Signal-to noise ratio: 75db or more

Sensitivity: -42dB±3dB (1dB=1V/Pa@1kHz)

· Operating Distance: 20m(without obstacle)

· Power Consumption: TX: 80mW RX: 60mW

· Working Time:

o TX: 4.5 hours * two times

o RX: 8 hours * two times

· Charing Time:

o TX:2 hours

o RX:2 hours

· Charging Case: 2 hours

· Charging Port(Charging Case): Type-C

Battery Capacity:

o TX:100mA

o RX:100mA

· Charging Case: 1000mA

	TOTAL			41,050.00
Purpose: For o	office uses.		·	
Checked by:	MICHAEL ANTHONY JAY	B. REGIS	Funds Available:	IAM. FLORES WIMC
	TWG - IT Supplies and Eq	uipment		BUDGET OFFICE (19)
Signature: Printed Name:	Requested by:	Noted by:	CO B. ALVIOLA	Approved by:
Designation:	END USER	UNIT HEAD,	PROJECT LEADER	PRESIDENT, VSU