

SCAN HERE



PR-2024-0119-171295



Republic of the Philippines  
**VISAYAS STATE UNIVERSITY**  
 Visca, Baybay City, Leyte

## PURCHASE REQUEST

PPMP No. : 231-1-1609-2024-0-0-0

PR No.: STF-2024-01-00184

Date: 01-19-2024

Dept./Office: **GS**

Category: **IT Supplies and  
Equipment**

Section/End-User: **Maricar B. Posas**Funding Source: **Special Trust Fund**Project Title/Code: **GS PPMP2024**

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	<b>Laminator</b>	pc	1	800.00		800.00
<b>Specification:</b> <ul style="list-style-type: none"> <li>A4 Hot and Cold Laminating Machine</li> </ul>						
2	<b>Rechargeable Wireless Keyboard and Mouse Set</b>	unit	2	950.00		1,900.00
<b>Specification:</b> <p>?Rechargeable Office Wireless Keyboard and Mouse Set</p> <p>?Size: 284*121*16.mm</p> <p>?Weight: 280g</p> <p>?Connection method: USB receiver/Bluetooth</p>						
3	<b>UPS, at least 800 watts</b>	unit	10	5,000.00		50,000.00
<b>Specification:</b> <p>?Recharging Time: at most 4 Hours</p>						
4	<b>VOIP Phone</b>	unit	5	6,000.00		30,000.00
<b>Specification:</b> <p>Audio Features</p> <ul style="list-style-type: none"> <li>HD voice: HD handset, HD speaker</li> <li>Smart Noise Filtering</li> <li>Narrowband codec: PCMU (G.711A), PCMA (G.711?), G.723.1, G.729, G.729A, G.729B, G.729AB, G.726, iLBC</li> <li>DTMF: In-band, Out-of-band (RFC 2833) and SIP</li> </ul> <p>INFO</p> <ul style="list-style-type: none"> <li>Full-duplex hands-free speakerphone with AEC</li> </ul>						

- VAD, CNG, AEC, PLC, AJB, AGC

#### Phone Features

- 2 VoIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Redial, call return, auto answer
- Local 5-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan
- XML Browser, action URL/URI
- Integrated screenshots
- RTCP-XR, VQ-RTCPXR
- Enhanced DSS Key

#### Directory

- Local phonebook up to 1000 entries
- Black list
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

#### IP-PBX Features

- Busy Lamp Field (BLF), Bridged Line Appearance

#### (BLA)

- Anonymous call, anonymous call rejection
- Hot-desking, voice mail

- Flexible seating
- Call park, call pickup
- Executive and Assistant
- Centralized call recording
- Visual voice mail
- Call recording

#### Display and Indicator

- 2.3" 132x64-pixel graphical LCD with backlight
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Power saving

#### Feature keys

- 2 line keys with LED
- 6 features keys: transfer, message, headset, redial, mute, hands-free speakerphone
- 5 navigation keys
- Volume control keys

#### Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 1\*
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

#### Other Physical Features

- Color: Classic Grey
- Wall mountable

- External Yealink AC adapter

AC 100-240 V input and DC 5 V/0.6 A output

- Power consumption (PSU): 2-3 W
- Power consumption (PoE): 3-4 W
- Dimension (W x D x H x T):  
188 x 189 x 162 x 50 mm
- Operating humidity: 10-95%
- Operating temperature: -10 to +45°C (+14 to 113°F)
- Storage temperature: -30 to +70°C (-22 to +158°F)

#### Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

#### Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)



- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS

#### DSCP

- SRTP for voice
- Transport Layer Security (TLS 1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Digest authentication
- OpenVPN, IEEE802.1X, L2TP VPN
- IPv6
- LLDP/CDP/DHCP VLAN
- ICE
- WPA2/WPA3
- Secure boot
- GARP (Generic Attribute Registration Protocol)

NOTE: Must be compatible with existing Yearstar S300 Server for auto provisioning

<b>TOTAL</b>										<b>82,700.00</b>	
Purpose: office use											
Checked by:						Funds Available:					
<b>DIONESIO I. ESTUPA</b>						<b>ALICIA M. FLORES</b>					
TWG - IT Supplies and Equipment						HEAD, BUDGET OFFICE					
Signature:	Requested by:			Noted by:			Approved by:				
Printed Name:	<b>MARICAR B. POSAS</b>			<b>CATHERINE C. ARRADAZA</b>			<b>DANIEL LESLIE S. TAN</b>				
Designation:	END USER			UNIT HEAD, PROJECT LEADER			OIC-PRESIDENT, VSU				