	Prepared by:	Note	d by:	100	IS Window Insta	Approved by:	
Signature: Printed Name:	RAFAEL ROSARIO A. JUN	TILLA	MARIC	NG BU	RLAS	PROSEIVY G. YE	PES
Designation:	WATEL ROGARION. OUR		JNIT HEAD,			PRESIDENT, VS	_
						- Ho monto	
					vs2 sw: 12w	?Power Output: rms 4.6v	
				(db)			
						78ass driver :4 inch	
						* 5 outlets (4 univer	
						* Output Capacity:	
						* Output (on batter)	
						* Input Power 220\	
						* Surjet 273 J	
						Battery recharge I	
				EC 80320		* No. of Oudets: 5 -	
						Battery Type: Lea	
		720				Web Camera for Lapto Desktop	
						?With clips for laptops an	
*							
						LATOT .	
					Plant Use		
	Chille						
101-10	ALICIA MIELORES				ESIO L ESTUI		
				inemgiu			



Republic of the Philippines VISAYAS STATE UNIVERSITY

Visca, Baybay City, Leyte

PURCHASE REQUEST

PPMP No.: PPMP-2024-052124-0137

PR No.: STF-2024-05-01164

Date: 05-22-2024

Dept./Office: ODPP

Section/End-User: Rafael Rosario A. Juntilla

Category: IT Supplies and

Equipment

Funding Source: Special Trust Fund

Project Title/Code: PPES/2024

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
	All-in-One Ink Tank Printer Wi-Fi Duplex with ADF	unit	2	21,000.00		42,000.00

Specification:

?Compact integrated tank design

?Print speeds up to 15ipm for black and 8.0ipm for colour

?Auto-duplex printing Fax and ADF capability / Ethernet &

?Wi-Fi Direct

?Borderless Printing up to A4 size

?Spill-free ink refilling

?Control Panel: 2.4 " Colour LCD Touch Panel

2 Computer Monitor	unit	1	8,000.00	8,000.00
--------------------	------	---	----------	----------

Specification:

Computer Monitor

Specification:

- Dimension 24"
- · Refresh rate 165 Hz
- Resolution 1920 x 1080 FHD
- · Brightness 400 cd
- Power Input DC 12v , 2.5 A
- Interface HDMI
- · Panel Type : Nano IPS

Desktop Computer (CPU only) for Modelling and Rendering - 16 OR 32 GB RAM DDR4 or Higher - 500 GB SS	lot	3	40,000.00	120,000.00
---	-----	---	-----------	------------

Specification:

- . 16 or 32 GB RAM DDR4 or Higher
- - 500 GB SSD
- 3.0 GHz or Higher CPU with compatible Motherboard and integrated graphics

Subvispec Pow Psig Pre R/I: PAUD PBas Pow Spec Web Desi Spec PAbu PS Pow	cification: ower Output: rms 4.5w×2 sw: 12w gnal to noise ratio: 80dba equency Response: 80hz~20khz (±0 li: 300±50mv sw: 100 ± 20mv lix/USB/SD card liss driver: 4 inch eble driver: 2 3/4 inch 6 1200VA-650W Uninterruptible liver Supply cification: • 5 outlets (4 universal, 1 IEC 603) • Output Capacity: 1200VA/650W • Output (on battery): 220V-240V, • Input Power: 220V-240V, 50/60F • Surje: 273 J • Battery recharge time: 8 hours • No. of Outlets: 5 - 4 universal, 1	unit 20 C13), 1 50/60Hz Hz +/- 5Hz	+/- 1Hz z (auto sensing)		18,000.00
?Pov ?Sig ?Fre ?R/I: ?Aux ?Bas ?Tre 5 UPS Pow Spec 6 Web Desi Spec ?Abo ?Wit	ower Output: rms 4.5w×2 sw: 12w gnal to noise ratio: 80dba equency Response: 80hz~20khz (±6 l: 300±50mv sw: 100 ± 20mv ox/USB/SD card ass driver: 4 inch eble driver: 2 3/4 inch 8 1200VA-650W Uninterruptible ver Supply cification: • 5 outlets (4 universal, 1 IEC 603) • Output Capacity: 1200VA/650W • Output (on battery): 220V-240V, • Input Power: 220V-240V, 50/60h • Surje: 273 J • Battery recharge time: 8 hours	unit 20 C13), 1 50/60Hz Hz +/- 5Hz	1200VA/650W, +/- 1Hz z (auto sensing)	AVR Technology, Surge Protection	
?Sig ?Fre ?R/I: ?Aux ?Bas ?Tre 5 UPS Pow Spec 5 Pow Spec ?Abd ?Wit	gnal to noise ratio: 80dba equency Response: 80hz~20khz (±6 1: 300±50mv sw: 100 ± 20mv ux/USB/SD card ass driver: 4 inch eble driver: 2 3/4 inch 8 1200VA-650W Uninterruptible ver Supply cification: • 5 outlets (4 universal, 1 IEC 603: • Output Capacity: 1200VA/650W • Output (on battery): 220V-240V, • Input Power: 220V-240V, 50/60h • Surje: 273 J • Battery recharge time: 8 hours	unit 20 C13), 1 50/60Hz Hz +/- 5Hz	1200VA/650W, +/- 1Hz z (auto sensing)	AVR Technology, Surge Protection	
Spec Spec Web Desi Spec ?Abord ?Wit	• 5 outlets (4 universal, 1 IEC 603. • Output Capacity: 1200VA/650W • Output (on battery): 220V-240V, • Input Power: 220V-240V, 50/60H • Surje: 273 J • Battery recharge time: 8 hours	20 C13), 1 50/60Hz Hz +/- 5Hz	1200VA/650W, +/- 1Hz z (auto sensing)	AVR Technology, Surge Protection	
6 Web Desi Spec ?Abo	 5 outlets (4 universal, 1 IEC 603) Output Capacity: 1200VA/650W Output (on battery): 220V-240V, Input Power: 220V-240V, 50/60H Surje: 273 J Battery recharge time: 8 hours 	50/60Hz Hz +/- 5Hz	+/- 1Hz z (auto sensing)		i, Easy to use
Spec ?Abo ?Wit	Dimension: 39 x 19 x 14 cm Battery Type: Lead-Acid Camera for Laptop and ktop	pcs	1	720.00	720.00
?Inte ?Fra ?Ima ?Brig	cification: cout 360 degrees, rotate up and down ith clips for laptops and desktops. ensor pixels: 2 million terface: USB 2.0 ame rate: 30 FPS tage sensor: CMOS ightness/color: automatically adjusts diditional features: built-in microphone		ees, you can ac	just the angle.	
	TOTAL				192,720.00
Purpose:	: For Office & Power Plant Use				
Checked				Funds Available:	A. FLORES & M-1CT