

SCAN HERE



PR-2023-1024-153159

OP NIS/2023 JUV



Republic of the Philippines
VISAYAS STATE UNIVERSITY
Visca, Baybay City, Leyte

PURCHASE REQUEST

PPMP No. : 228-1-1038-2024-7-0-0

PR No.: STF-2023-10-02625

Date: 10-24-2023

Dept./Office: UR

Category: IT Supplies and
Equipment

Section/End-User: Homer Lois P. Napoles

Funding Source: Special Trust Fund Project Title/Code: STF - ID Fee

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	Dual-Sided Thermal ID Card Printer	unit	1	152,000.00		152,000.00
Specification:						
• Dual Sided Printing • Direct Dye-Sublimation • Edge to Edge • 300 dpi (Colour & Mono); 600dpi & 1200dpi (Mono only) • Automatic Card Feeding • ISO CR80 or ISO CR79 (Option-Factory installed) • 0.38mm (15mil) ~ 1.0mm (40mil) • PVC, PET, Composite PVC • Monochrome - 5 sec/card (720 cards/hour) • YMCKOK - Max. 22 sec/card (164 cards/hour) • Input Card Hopper - 100 Cards / 200 Cards with cover open • Output Card Hopper - Front : 40 Cards / Rear : 100 Cards (Optional Rear-side Stacker) • 64MB RAM Memory • Interface - 2 Line LCD / 2 LED Buttons • Supported Platforms - Microsoft Windows 7/8/10, Mac OS, Linux • Communication - USB, Ethernet (Option), WiFi (Option) • Power Supply - Free Voltage (AC100/220V, 50~60Hz) • Power Consumption - 48W						
2	Epson 003 Ink Bottle for Epson L3150, Black	btls	25	400.00		10,000.00
Specification:						
Epson 003 Ink Bottle for Epson L3150, Black						
3	Epson 003 Ink Bottle for Epson L3150, CYAN	btls	25	400.00		10,000.00

OP

Specification: Epson 003 Ink Bottle for Epson L3150, CYAN				
4	Epson 003 Ink Bottle for Epson L3150, MAGENTA	btls	25	10,000.00
Specification: Epson 003 Ink Bottle for Epson L3150, MAGENTA				
5	Epson 003 Ink Bottle for Epson L3150, YELLOW	btls	25	10,000.00
Specification: Epson 003 Ink Bottle for Epson L3150, YELLOW				
6	Mirrorless Camera, 24.1MP, 3" LCD Monitor, 4K Video	unit	1	54,000.00
Specification: • AF Modes - Stills: One-Shot AF, Servo AF, Manual Movie recording: One-Shot AF, Movie Servo AF, Manual • AF Point Selection - Automatic selection, Manual selection • AF System Points - Stills: Max. 3975 selectable AF point positions / Up to 143 zones (auto selection) Movie recording: Max. 3375 selectable AF point positions / Up to 117 zones (auto selection) • Built-in Flash • Closest Focusing Distance (cm) - 25 • Continuous Shooting Speed (Shots Per Sec) (Up To) - 10 (One-Shot AF) / 7.4 (Servo AF) • Digital Zoom - Approx. 3-10x (for movie recording only) • Drive System - Stepping Motor-driven lead screw + rack system • Effective ISO - Stills: 100 - 25,600 (H:51,200), Movie (full HD/HD): 100 - 12,800 (H: 25,600), Movie (4K): 100 - 6,400 • Exposure Compensation - ±3 stops in 1/3-stop increments, AEB: ±2 stops in 1/3-stop increments • Eye Detection AF - One-Shot AF / Servo AF / Movie Servo AF • Flash Modes - E-TTL II Autoflash, FE Lock, Manual pop-up, Retractable, Built-in • Focal Length (35mm Equivalent) - 24 - 72mm(3x) • Guide Number ISO 100 metres - 5 • Image Resolution - 6000 x 4000 (L), 3984 x 2656 (M), 2976 x 1984 (S1), 2400 x 1600 (S2), 6000 x 4000 (RAW/C-RAW) • Image Stabilizer - Stills: Lens shift type, Movie recording: Lens shift type & In-body 5-axis electronic image stabilization (movie recording only) • with Manual Focus • Memory Card Type - SD, SDHC*, SDXC*, *UHS-I cards compatible • Metering Mode - Stills: Evaluative, Partial, Spot, Center-weighted average, Movie: Evaluative (when faces are detected with [Face+Tracking]), Center-weighted average (when no faces are detected) • Processor Type - DIGIC 8 • Sensor Size - APS-C • Shooting Modes - Stills: Scene Intelligent Auto, Hybrid Auto, Special scene modes (Self Portrait, Portrait, Smooth Skin, Landscape, Sports, Panning, Close-up, Food, Night Portrait, Handheld Night Scene, HDR Backlight Control, Silent Mode), Creative filters (Rainy BW, Soft focus, Fish-eye effect, Water painting effect, Toy camera effect, Miniature effect, HDR art standard, HDR art vivid, HDR art bold, HDR art embossed), Program AE, Shutter-priority AE, Aperture-priority AE, Manual Exposure, Movie recording: Movie auto exposure, Movie manual exposure • Shutter Speed Range (Sec.) - Stills: 30 - 1/4000, Bulb, Movie recording: 1/25 - 1/4000 (PAL) or 1/30 - 1/4000 (NTSC) • Standard Power Supply - LP-E12 • Silent Shutter - Available: Single Shot				

• Still Image Format - JPEG, RAW, RAW + JPEG, C-RAW, C-RAW+JPEG • Viewfinder Coverage (Approx.) - 100% • Viewfinder Type - 0.39-inch OLED, 2.36million dots, 59.94fps refresh rate • White Balance - Auto (Ambience priority), Auto (White priority), Preset (Daylight, Shade, Cloudy, Tungsten light, White fluorescent light, Flash), Custom, Color temperature setting (approx. 2500-10000 K), White balance correction and white balance bracketing features provided, *Flash color temperature information transmission possible • X-sync (sec.) - 1/200					
7	Photography Camera Tripod, Lightweight	unit	1	3,000.00	3,000.00
Specification: Compatible with Mirrorless Camera (Canon, Nikon, Fuji, Pentax, etc.)					
8	PVC Card Blank, 500 pcs/box, Smart ID Machine, Plain White	boxes	5	1,250.00	6,250.00
9	PVC Card Blank, 500 pcs/box, Smart ID Machine, with MAGSTRIPE	boxes	5	2,250.00	11,250.00
10	Solid State Drive, Internal, 2.5", 1TB	unit	4	3,000.00	12,000.00
Specification: • SATA Rev. 3.0 (6GB/s) with backward compatibility to SATA Rev. 2.0 (3GB/s) • Up to 500MB/s read and 450MB/s write or better					
11	YMCKOK Ribbon Kit for Smart 50 ID Machine	boxes	7	6,800.00	47,600.00
Specification: Refill for Smart 50 ID Machine					
12	YMCKOK Ribbon Kit for Smart 51 ID Machine	boxes	7	6,800.00	47,600.00
Specification: Refill for Smart 51 ID Machine					
TOTAL					373,700.00
Purpose: For office use.					
Checked by:		DIONESIO I. ESTUPA		Funds Available:	
TWG - IT Supplies and Equipment		Noted by:		HEAD, BUDGET OFFICE	
Signature:	Requested by:	MIRIAM M. DE LA TORRE		Approved by:	
Printed Name:	HOMER LOIS P. NAPOLES	MARVEN A. CASTAÑEDA		DANIEL LESLIE S. TAY	
Designation:	END USER	UNIT HEAD, PROJECT LEADER		EDGARDO E. TULIN	

014
11/9/2