

SCAN HERE



PR-2023-0712-129783

07/20/23

TO DBS



Republic of the Philippines  
**VISAYAS STATE UNIVERSITY**  
 Visca, Baybay City, Leyte

## PURCHASE REQUEST

PPMP No. : 5-1-2097-2023-5-0-4

PR No.: STF-2023-07-01157

Date: 07-12-2023

Dept./Office: DBS

Category: **Laboratory  
Equipment**

Section/End-User: Alma . Gofredo

Funding Source: **Special Trust Fund**Project Title/Code: **STF Instruction 2023**

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	<b>Compound Binocular Microscope</b>	piece	5	32,000.00	ANALYN M. MAZO	160,000.00

### Specification:

- Head: 45° Inclined Binocular, 360° rotation
- Eyepiece: 10x Wide Field Eyepiece
- Nosepiece: 4 Position
- Optical Magnification Range: 40 to 1000x
- Objectives: 4x, 10x, 40x, 100x
- - Achromatic Optics
- Mechanical Stage/ Slide Holder: 5.5 x 5.5 inches
- Focusing: Coarse and Fine
- Illumination: Halogen Illumination
- Dimmer: Yes
- Body Frame: Metal frame with Gray Finish
- Weight: Approximately 12.3 lb / 5.5 kg

2	<b>Multiparameter ph/ORP/EC/TDS/Salinity/DO/Pressure/Temperature Waterproof Meter</b>	unit	1	150,000.00	ANALYN M. MAZO	150,000.00
---	---	------	---	------------	----------------	------------






### Specification:

- A waterproof portable logging multiparameter meter that monitors up to 12 different water quality parameters.
- Multi-sensors probe allows for the measurement of key parameters including pH, ORP, conductivity, dissolved oxygen, and temperature.
- The probe transmits readings digitally to the meter, where data points can be displayed and logged.
- The complete system is simple setup.
- **Backlit graphic LCD Display**- features a backlit graphic LCD with on-screen help and the capability to display up to twelve parameters simultaneously.
- The graphic display allows for the use of virtual keys to provide for an intuitive user interface
- **Waterproof protection**-the meter is enclosed in an IP67rated waterproof casing and can withstand immersion in water at a depth of 1m for up to 30 minutes. The probe features an IP68 rating for continuous immersion in water
- **Quick Connect digital Probe**-The probe features a quick connect DIN connector that makes a waterproof connection with the meter.
- **Color Coded, Field Replaceable sensors**-sensor replacement is quick and easy with field replaceable, screw-type connectors that are color-coded for easy sensor port identification

- **Auto-sensor recognition-** The probe and meter automatically recognize the sensors that are connected. Any ports not used on the probe will not have the parameter displayed or be configurable
- **Automatic temperature compensation-**Integrated temperature sensor allows for automatic temperature compensation of pH, conductivity and dissolved oxygen measurements
- **Automatic Barometric pressure compensation-**The meter features a built-in barometer with user selectable units for dissolved oxygen pressure compensation
- **Standard or quick calibration-**Quick calibration provides a speedy, single-point calibration for pH, conductivity, and dissolved oxygen. Standard pH calibration options are available for calibrating up to three points from a selection of five standard buffers and one custom buffer. Conductivity calibration is a single point from six standard selections or one custom standard. Dissolved oxygen calibration is up to two standard points or a single custom point
- **GLP Data-** includes a GLP feature that allows users to view calibration data and expiration information at the touch of a key. Calibration data includes date, time, buffers/standards used for calibration, and slope characteristics
- **Data Logging-**Allows users to store up to 45,000 continuous log-on demand samples with logging intervals from one second to three hours
- **Intuitive Keypad-**The fitted rubber keypad has dedicated keys for power, backlight, up/down arrows, help and alphanumeric characters. The meter also features two virtual soft keys that navigate the user through the configuration of each parameter, meter setup, and logging of data. The interface is intuitive for any user's level of experience.
- **Dedicated help key-** Contextual help is always available through a dedicated "HELP" key. Clear tutorial messages and directions are available on-screen to quickly guide users through setup and calibration. The help information displayed is relative to the setting/option being viewed.
- **PC Connectivity-** Logged data can be transferred to the Window's compatible PC with the included micro USB cable and software
- **Long Battery Life-** The display of the meter has a battery icon indicator to show the remaining power. The meter uses four 1.5V AA batteries that provide up to 360 hours of battery life
- **Rugged Thermoformed Carrying case-** The meter, probe and all accessories are supplied in a rugged carrying case designed to provide years of use. The inside compartment of the carrying case is thermoformed to securely hold and protect all of the components.

	TOTAL					310,000.00
--	-------	--	--	--	--	------------

Purpose: for Laboratory use

Checked by:  <b>ELIZABETH S. QUEVEDO</b>		Funds Available:  <b>ALICIA M. FLORES</b>	
TWG - Laboratory Equipment		HEAD, BUDGET OFFICE	
Signature: Printed Name: Designation:	Requested by:  <b>ALMA J. GOFREDO</b> END USER	Noted by:  <b>ANALYN M. MAZO</b> UNIT HEAD, PROJECT LEADER	Approved by:  <b>EDGARDO E. TULIN</b> PRESIDENT, VSU

7	20	22
---	----	----