

Specification:

NEMA, customized surface-mounted panel, metal enclosure, GI Sheet #16, powder coated wrinkle gray color, corrosion resistant & pure copper busbar with grounding terminal lugs & neutral bus bolt-on type.

Main: 1-80AT/80AF, 2P, 240 volt, 15 kAIC MCB

Branches: 6- 30AT, 10 kAIC, 240 volts, 2P 60 Hz MCB

7	UFO led Highbay Lights 200 WATT, 6500k (Day light) 25300 Lumens	pcs	30	13,000.00		390,000.00
---	--	-----	----	-----------	--	------------

Specification:

UFO LED Highbay Lights 200 watts, 6500k (Daylight) 25300 Lumens



Wattage: 200 watts, Lamp type: LED, Lumens: 25300

Color Temperature: 6500k-Daylight, Color Rendering Index: 80, Beam angle: 110 deg.

Rated Average Life: 30000 hours, Power Supply: 220-240 50/60 Hz

	TOTAL					556,000.00
--	--------------	--	--	--	--	-------------------

Purpose: For VSU gym lightings

Checked by:  PHLOEM D. GALUPO		Funds Available:  for ALICIA M. FLORES <i>my. electrical</i> HEAD, BUDGET OFFICE	
TWG - Construction and Electrical Supplies			
Signature:	Requested by:  RAFAEL ROSARIO A. JUNTILLA	Noted by:  MARLON G. BURLAS	Approved by:  EDGARDO E. TULIN
Printed Name:			
Designation:	END USER	UNIT HEAD, PROJECT LEADER	PRESIDENT, VSU



Republic of the Philippines
VISAYAS STATE UNIVERSITY
Visca, Baybay City, Leyte

SCAN HERE



PR-2023-0403-109148

4/11/23

PURCHASE REQUEST

PPMP No. : 176-1-1557-2023-2-0-24

PR No.: STF-2023-04-00574

Date: 04-03-2023

Dept./Office: **ODPP**

Category: **Construction
and Electrical Supplies**

Section/End-User: **Rafael Rosario A. Juntilla**

Project Title/Code: **GYM PPES**

Funding Source: **Special Trust Fund**

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	Electrical (PVC) Long Sweep Elbow, 3/4" x 90deg	pcs	30	75.00		2,250.00
2	Electrical Conduit, (PVC) Orange, 3/4"(25mm) x 3m	length	200	160.00		32,000.00
Specification: Sched 40, Durable, Good Quality						
3	Electrical Tape, Vinyl	rolls	10	75.00		750.00
Specification: ?Flame retardant and compatible with plastic cable and wire harness insulations ?Flexible PVC with aggressive rubber adhesive ?Primary electrical insulation for all wire and cable splices rated up to 600 volts. ?19mm x 16m x 0.155mm ?Heavy Duty ?ASTM approved						
4	Electrical Wire, THHN / THWN, AWG 10 (5.5mm2), Stranded, 150 meters/box	boxes	6	8,500.00		51,000.00
Specification: ?Building Wire ?Stranded with Nylon Insulation ?Gauge 10 ?UL listed						
5	Electrical Wire, THHN / THWN, AWG 4 (22mm2), Stranded	roll	2	25,000.00		50,000.00
Specification: • Stranded Copper with Nylon Insulation • Gauge 4 • UL listed						
6	NEMA, Customized surface-mounted panel, metal enclosure, GI Sheet # 16, powder coated	unit	1	30,000.00		30,000.00