



Republic of the Philippines
VISAYAS STATE UNIVERSITY
 Visca, Baybay City, Leyte

PURCHASE REQUEST

PPMP No. : **PPMP-2025-092524-0594**

PR No.: **STF-2025-02-00156**

Date: **02-24-2025**

Dept./Office: **DOH**

Category: **Laboratory
Equipment**

Section/End-User: **Aljay D. Valida**

Project Title/Code: **Procurement 2025 - DOH lab share**

Funding Source: **Special Trust Fund**

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	Brix / Acidity Meter	pc	1	42,000.00		42,000.00

Specification:

- **Measurement Range:**
 - **Brix:** 0.0 to 60.0%
 - **Acidity:**
 - 1L (Low Acidity Citrus): 0.10 to 4.00%
 - 1H (High Acidity Citrus): 2.50 to 8.80%
 - 2 (Grape & Wine): 0.10 to 4.00%
 - 3 (Tomato): 0.10 to 3.00%
 - 4 (Strawberry): 0.10 to 3.50%
 - 5 (Blueberry): 0.10 to 4.00%
- **Temperature Range:** 10.0 to 40.0°C

2	OHAUS™ Valor™ 1000 - V12P Scales	unit	2	20,000.00		40,000.00
---	---	------	---	-----------	--	-----------

Specification:

Specifications:

- **Model:** V12P30
- **Capacity:** 30 kg (60 lb.)
- **Readability:** 0.01 lb. (5 g)
- **Resolution:** 1:6,000 (Pounds)
- **Weighing Modes:** Gram, Kilogram, Pound, Ounce, Pound/Ounce

Display:

- **Type:** Backlit LCD
- **Stabilization Time:** ? 2 sec.

Construction:

- **Material:** Stainless Steel (Platform)
- **Housing:** ABS
- **Includes:** Integrated Level Bubble, Adjustable Feet, Selectable Auto-Off, Selectable Weighing Units, In-Use Cover,

Integrated Carrying Handles for Easy Transportation

Dimensions:

- **Pan Length:** 245 mm (9.65 in.)
- **Pan Width:** 190 mm (7.48 in.)
- **Depth:** 260 mm
- **Overall Dimensions (L x W x H):** 270 x 260 x 122 mm (10.6 x 10.2 x 4.8 in.)
- **Weight:** 2.5 kg (5.5 lb.)

Temperature:

- **Operating Range:** 0°C to 40°C (32°F to 104°F)

Battery:

- **Type:** 4 D (Sold Separately)
- **Battery Life:** Up to 1500 Hours

Power Requirements:

- **AC Power Adapter:** Included

Calibration:

- **Type:** External Digital Calibration Software






Certifications/Compliance:

- NSF
- USDA-AMS

Additional Features:

- **Electrical Requirements:** AC Power Adapter included
- **Temperature Operating Range:** 0°C to 40°C (32°F to 104°F)

The OHAUS Valor 1000 V12P is designed for precise and durable weighing applications, offering easy portability and robust functionality.

TOTAL		82,000.00	
Purpose: 2025-DOH-03 Establish greater and wider internationalization, performance and global reputation.			
Checked by:  GENESIS C. ALBARICO		Funds Available:  ALICIA M. FLORES	
TWG - Laboratory Equipment		HEAD, BUDGET/OFFICE	
Signature:	Prepared by: 	Noted by: 	Approved by: 
Printed Name:	ALJAY D. VALIDA	ALJAY D. VALIDA	PROSE IVY G. YEPES
Designation:		UNIT HEAD, PROJECT LEADER	PRESIDENT, VSU